

PRODUCT SPECIFICATIONS

PRODUCT COMPOSITION	DATA	
Style Description:	Standard: Fine Rib; Optional Sponge Backing: Fine Rib/Anti-Fatigue	
Surface Aspect:	Black Vinyl	
Backing:	Standard - Smooth; Optional - Closed Cell Vinyl Sponge	
PRODUCT DIMENSIONS		
Thickness	Standard - 1/8"; Optional Sponge Backing 1/2"	
Standard Sizes	Full rolls or custom sizes only	
Roll Sizes	3 x 105, 4 x 105	
Custom Sizes	3' and 4' widths by custom lengths to 105'. Maximum 60' length for Optional Sponge Backing	
Colors	Black Only	
PHYSICAL PROPERTIES	MD Spec Initial	MD Spec 70h @ 70°C Heat Aged
Tensile Strength (kN/M) ASTM D412 Die A	10,340	10,340
Tear Strength (kN/M) ASTM D624 Die C	35	35
Elongation (%) ASTM D412 Die C	225	160
Hardness Shore A ASTM D2240 15s Delay	83 ± / -6	
Resistance to Wear ASTM D3389	Maximum Allowable Loss = 76 mm ³	
Cold Flex (5h/-29° C/1" mandrel)	Mat must withstand a 180° flex around 25mm mandrel @ -29° C with no evidence of cracking	
FLAMMABILITY PROPERTIES	Requirement ≤4	

COMMON USES

- Indoor or outdoor walkways.

*Sponge backing - not recommended for wet areas.

CLEANING & MAINTENANCE

Dry Areas: Sweep and then mop the Corrugated Runner with a Neutral cleaner.

Periodic Maintenance: If severely soiled, scrub mat using a brush with a low foaming general purpose cleaner. Flush mat with hot water and allow to dry flat before placing it back into service.

**For more detailed procedures contact our trained Product Specialist or visit our website at www.matsinc.com*

WARRANTY

Limited 1-Year Warranty. Mats, Inc. guarantees its Anti-fatigue Mats against deterioration due to faulty materials or workmanship. This guarantee does not cover damage that could occur from other abuses beyond the general intended application of the product. No other warranty is expressed or implied. Limit of liability from any losses resulting from the use of this product shall be for the purchase price only, and applied in form of credit, excluding any freight charges.