

Cushion Eze

Heavy-duty Construction Provides Years of Performance

PRODUCT SPECIFICATIONS	
PRODUCT COMPOSITION	DATA
Description:	Styrene rubber (SBR).
Surface Aspect:	Marbleized High-Grade Top Surface
Primary Backing:	Resilient Sponge Backing
PRODUCT DIMENSIONS	
Thickness	3/8", ½"
Standard Sizes	18" x 30", 18" x 48", 2 x 3, 3 x 4, 3 x 5, 36" x 64"
Roll Sizes	2 x 60, 3 x 60, 4 x 60
Custom Sizes	2', 3' and 4' widths by custom lengths to 60'
Colors	Green, Light Gray, Black, Brown, Beige, Dark Gray, Blue, Terra-Cotta, White
PHYSICAL PROPERTIES	
Bearing Load	150 lbs per square inch
Static Load	Floor protectors should be chosen so that stationary loads do not exceed 150 lbs. per sq. inch.
FLAMMABILITY PROPERTIES	Meets the flammability requirement of DOC FF-170 (Pill Test)

COMMON USES

- Work Stations
- Cash Registers
- Service Counters
- Salons
- Industrial Settings

CLEANING & MAINTENANCE

Dry Areas Only: Sweep and then mop the Cushion Eze Mat with a Neutral cleaner.

Periodic Maintenance: If severely soiled, scrub mat using a brush with a low foaming general purpose cleaner. Mop mat with hot water and allow to dry flat before placing it back into service.

WARRANTY

Limited 1-Year Warranty. Mats, Inc. guarantees its Anti-fatigue Mats against deterioration due to faulty materials or workmanship. This guarantee does not cover damage that could occur from other abuses beyond the general intended application of the product. No other warranty is expressed or implied. Limit of liability from any losses resulting from the use of this product shall be for the purchase price only, and applied in form of credit, excluding any freight charges.

^{*}Not recommended for wet areas.

^{*}For more detailed procedures contact our trained Product Specialist or visit our website at www.matsinc.com