

Promessa® Collection



MARINE



HOSPITALITY



OFFICE



RESIDENTIAL



AVIATION



RECREATION



DENTAL



HEALTHCARE

Durable, Luxurious, Antimicrobial Protection

Promessa combines extreme durability with naturally bonded with an **EPA registered, silver-based antimicrobial** agent, making it ideal for healthcare and other high wear applications. It meets or surpasses industry wear standards including bond strength, seam strength and tear strength. Promessa exceeds 400,000 double rubs on the Wyzenbeek abrasion test method showing no wear and tear—that's 13X heavy-duty industry standards.

You've Only Touched the Surface

Promessa stays cool to the touch, even when exposed to sunlight. Soft and supple, Promessa is tough enough to withstand kids and pets. Because it's inherently stain-resistant, no toxic aftercare is required to keep Promessa looking its best.

Earth Friendly

- Greenguard® Certified
- No PVC (Polyvinyl Chloride)
- No POPs (Persistent Organic Pollutants)
- No PBDEs (Polybrominated Diphenyl Ethers)
- No HFRs (Halogenated Flame Retardants)
- Meets the most stringent VOC standards
- No Plasticizers, Heavy Metals, Stabilizers, Phthalates or Bisphenol A (BPA)
- No toxic by-products
- Over 99% of solvents recaptured and recycled
- ISO 9001 Certified Mill

Maintenance & Care Instructions

Keep Ultrafabrics, LLC brand surfaces looking great by routine and proper maintenance. Clean regularly to prevent excessive dirt from accumulating. Follow these guidelines to extend the life of the fabric:

- Clean regularly with soap and water
- Wipe up spills as soon as they occur
- Remove stains with alcohol-based cleaners like Fantastik® and Formula 409®
- Clean/disinfect using a 5:1 water/bleach solution or a commonly used healthcare disinfectant, such as **CaviCide®** and **Virox®**
- Thoroughly rinse all solution residue with water
- Air dry

For more detailed information, visit us on the web at www.ultrafabricsllc.com

SPECIFICATIONS

ISO 9001-CERTIFIED PRODUCTION FACILITY

COMPOSITION:	100% POLYURETHANE SURFACE 65% POLYESTER, 35% RAYON BACKING
WEIGHT:	APPROX. 12 OZ. PER SQUARE YD (APPROX. 410 GRAMS PER SQUARE METRE) APPROX. 18 OZ. PER LINEAR YD (APPROX. 560 GRAMS PER LINEAR METRE)
THICKNESS:	APPROX. 1.1 MM
WIDTH:	54 INCHES / 137 CENTIMETRES
PUT-UP:	APPROX. 30 YDS / 27.5 METRES R.O.T.

CHARACTERISTICS (MEETS OR EXCEEDS)

ABRASION:	ASTM D 4157 / 400,000 DOUBLE RUBS* BS 2543 / 180,000 RUBS** *WYZENBEEK **MARTINDALE
TENSILE STRENGTH:	ASTM D 1117
TEAR STRENGTH:	ASTM D 1117
DIMENSIONAL CHANGE:	ASTM D 3597
SEAM STRENGTH:	ASTM D 751
STRETCH & SET:	SAE J855
ANTIMICROBIAL	ASTM E 2180

COLORFASTNESS

CROCKING:	AATCC 8, CLASS 5 DRY & 5 WET
LIGHT	AATCC 16E, AATCC 16A, CLASS 4 – 5 ISO 105 - B02 : 1999 GRADE 7/8
GAS:	AATCC 23, CLASS 5
OZONE:	AATCC 109, CLASS 5

F/R RATING: (HFR FREE)

ASTM E 84 (ADHERED)	CLASS A
CA 117 E	CLASS 1
FMVSS 302 & 95/28 ANNEX IV	PASS
NFPA 260	CLASS 1
UFAC	CLASS 1

• CAN BE TREATED TO MEET FAR SPECIFICATIONS.
• THIS FABRIC, WHEN TREATED AND/OR USED WITH OTHER COMPATIBLE FURNITURE COMPONENTS, HAS BEEN SHOWN TO PERFORM WELL UNDER THE FIRE TEST CONDITIONS OF CALIFORNIA TECHNICAL BULLETIN 133, BS 5852 PT 0, 1 & 5 (CRIB 5), IMO A.652 (16), BS 7175 AND BS 5867 PART 2 TYPE B.



Scan code to place sample request



CRAFTED INTELLIGENCE.

Ultrafabrics, LLC | Hudson Point, 303 South Broadway | Tarrytown, NY 10591 | USA | T 914.460.1730 | F 914.631.3572 | www.ultrafabricsllc.com

Ultrafabrics Europe Ltd. | 19 The Warren, East Gosport | Leicestershire, LE7 3XA | United Kingdom | T +44.116.260.9625 | ufe@ultrafabricsllc.com

Made in Japan. Ultra-leather™, Brisa® and Promessa® are trademarks of Ultrafabrics, LLC.

7/12

