Raffia





















337-3991 Linen



337-3001 Durango Dust



337-3992 Sandstone



337-5832 Highrise





Raffia Collection













Durable, Beautiful, Contemporary Appeal

Raffia gives you the exceptional combination of stylish good looks and the strength to stand up to your active lifestyle. It meets or surpasses industry wear standards including bond strength, seam strength and tear strength. Raffia exceeds 400,000 double rubs on the Wyzenbeek abrasion test method showing no wear and tear—that's 13X heavy-duty industry standards.

You've Only Touched the Surface

Raffia stays cool to the touch, even when exposed to sunlight. Soft and supple, Raffia is tough enough to withstand kids and pets. Because it's inherently stain-resistant, no toxic aftercare is required to keep Raffia looking its best.

Earth Friendly

- Greenguard[™] Certified
- No PVC (Polyvinyl Chloride)
- No POPs (Persistent Organic Pollutants)
- No PBDEs (Polybrominated Diphenyl Ethers)
- No HFRs (Halogenated Flame Retardants)
- Meets the most stringent VOC standards
- No Plasticizers, Heavy Metals, Stabilizers, Phthalates or Bisphenol A (BPA)
- No toxic by-products
- Over 99% of solvents recaptured and recycled
- ISO 9001 Certified Mill

Maintenance & Care Instructions

Keep Ultrafabrics, LLC brand surfaces looking great by routine and proper maintenance. Clean regularly to prevent excessive dirt from accumulating. Follow these guidelines to extend the life of the fabric:

- Clean regularly with soap and water
- Wipe up spills as soon as they occur
- Remove stains with alcohol-based cleaners like Fantastik[®] and Formula 409[®]
- Disinfect using a 5:1 water/bleach solution or a commonly used healthcare disinfectant, such as CaviCide® and Virox®
- Thoroughly rinse all solution residue with water
- Air dry

SPECIFICATIONS

COMPOSITION:	100% POLYURETHANE SURFACE 100% REINFORCED RAYON BACKING
WEIGHT:	APPROX. 9.5 OZ. PER SQUARE YD (APPROX. 320 GRAMS PER SQUARE METRE
	APPROX. 14.3 OZ. PER LINEAR YD (APPROX. 440 GRAMS PER LINEAR METRE)
THICKNESS:	APPROX. 1.0 MM
WIDTH:	54 INCHES / 137 CENTIMETRES
PUT-UP:	APPROX. 30 YDS / 27.5 METRES R.O.T.
CHARACTERISTICS (
ABRASION:	ASTM D 4157 / 400,000 DOUBLE RUBS* BS 2543 / 180,000 RUBS** *WYZENBEEK **MARTINDALE
TENSILE STRENGTH:	ASTM D 1117
TEAR STRENGTH:	ASTM D 1117
DIMENSIONAL CHANGE:	ASTM D 3597
SEAM STRENGTH:	ASTM D 751
STRETCH & SET:	SAE J855
COLORFASTNESS	
CROCKING:	AATCC 8, CLASS 5 WET & DRY
LIGHT	AATCC 16E, AATCC 16A, CLASS 5
GAS:	AATCC 23, CLASS 5
OZONE:	AATCC 109, CLASS 5

- · CAN BE TREATED TO MEET FAR SPECIFICATIONS.
- THIS FABRIC, WHEN TREATED AND/OR USED WITH OTHER COMPATIBLE FURNITURE COMPONENTS, HAS BEEN SHOWN TO PERFORM WELL UNDER THE FIRE TEST CONDITIONS OF CALIFORNIA TECHNICAL BULLETIN 133 AND BS 5852 SOURCE 5 ("CRIB 5"), IMO A.652(16), BS 7175 AND BS 5867 PART 2 TYPE B.

CA 117 E

UFAC

FMVSS 302

NFPA 260

ASTM E 84 (ADHERED)

For more detailed information, visit us on the web at www.ultrafabricsllc.com



CLASS A

PASS

CLASS 1

CLASS 1





ULTRA SURFACES. ULTRA RELEVANT.

Ultrafabrics, LLC | Hudson Point, 303 South Broadway | Tarrytown, NY 10591 | USA | T 914.460.1730 | F 914.631.3572 | www.ultrafabricsIlc.com
Ultrafabrics Europe Ltd. | 19 The Warren, East Goscote | Leicestershire, LE7 3XA | United Kingdom | T +44.116.260.9625 | ufe@ultrafabricsIlc.com
Made in Japan. Ultraleather™, Brisa® and Promessa® are trademarks of Ultrafabrics, LLC.





