

FEATURES	
Installation type	- Freestanding - Theatre Stage™
No. of bathers	2
Raised seats	2
Heated backrests (Independently controlled)	2
Heated headrests	2
Inverted V	2
Armrests	4
Grab bars (color match)	2
Drain & overflow	Inst. & incl.
Control	MiaPlus
ThermoMasseur® bath	\$
Soaker bath	N/A

Sound Therapy (Euphonia® headset)		\$		
COLO	RS			
Stand	ards			
White	Bone	Biscuit	Almond	
Option	nals			\$
Black	Mexican sand	Cashmere	Sandbar	Gray
WAR	RANTY			
Contr	ols*			5 years
Rath 2	& turbine*			20 years



PERSONALIZE YOUR BATH

- 1 Choose the bath color from standard or optional colors.
- 2 Choose the base color same as bath color or wood finish.
- 3 Choose the exterior shell color from standard or optional colors.





AMMA OVAL 7242 (FREESTANDING) 72 x 42 x 28

ACCESSORIES - OPTIONAL


Clear acrylic grab bars	With Chrome, Brass or Brushed nickel inserts	\$	
cicai acijiic graz zaic	Trial direction Diagonal months moonto	Ψ	

Control	MiaMulti \$
Cutting template	# 90000036 (drop-in, freestanding) # 90000059 (theatre stage)
Others	- There is a height difference for the flat deck (see drawing Detail A) Turbine located under bath and accessibl by a removable base cover Faucets might be installed on deck of bath. Overflow preinstalled for easier in-home fitting Specify flat or raised deck.

TOTAL PRICE

\$

Freestanding installation




LETTER	DESCRIPTION	MEASURE
A	Outside edge to center drain	13 1/2"
В	Outside edge to overflow	5 3/8"
С	Total length	72"
D	Total width	42"
E	Bathing well length	52 1/4"
F	Bathing well width at foot area	21 3/8"
G	Raised seat length	18 5/8"
Н	Raised seat width	24"
ı	Flat surface width	3 7/8"
J	Deck width	5 1/4"
K	Total height to headrest	29 7/8"
L	Height from bottom of tub to top deck	27 5/8"
M	Height from bottom of lip to top deck	2"
N	Height from drain to center of overflow	18 1/8"
0	Maximum water level	16 3/8"
P	Slope of backrest	18°

Indicates turbine position

■ Indicates LED light position

• Indicates control position when factory-installed

Theatre Stage™ installation



Q	Height from bottom of tub to top deck	29 7/8"
R	Base length	56 1/2"
S	Stage height	10"
T	Base width	36 1/2"

AMMA OVAL 7242 FREESTANDING TECHNICAL SPECIFICATIONS

755 W

1000 W

Approx. shipping weight	290 lbs
Imp. gallons	54
US gallons	65
Jets	58

Hot water supply required	Should be 70% of water capacity of tub or greater.
Turbine access	Remove decorative skirt to access the turbine. Must be at least 19" x 22" to access the turbine. Must be connected to a 20 A. 120 V, 60 Hz, protected by a ground-fault circuit interrupter (GFCI) on a dedicated line. Air vent necessary, 2" X 4" minimum.

Our products must be installed by certified professionals only and according to our Owner's Manual as well as federal, provincial/state and local building codes and regulations (www.bainultra.com/documentations).

Turbine power

Air heater

1 800 463.2187 9 From 8 a.m. to 8 p.m. Monday to Thursday (EST) . From 8 a.m. to 5 p.m. on Friday (EST)