

FEATURES	
Installation type	Freestanding
No. of bathers	1
Raised seat	1
Heated backrest	1
Heated headrest	1
Inverted V	1
Armrests	2
Grab bars (color match)	2
Drain & overflow	Inst. & incl.
Wooden or acrylic insert	Incl.
Control	MiaMulti
ThermoMasseur® bath	\$
Soaker bath	N/A

THERAPIES	
Chromatherapy 3-LED	
Sound Therapy (Euphonia™ System)	\$

COLO	RS				
Standa	ards				
White	Bone	Biscuit	Almond		
Option	als			\$	
Black	Mexican sand	Innocent blush	Cashmere	Sandbar	Gray
Woode	en or acry	/lic inser	t	The state of the s	
				The state of	
Wood	Eclipse	Onyx	Galaxy	Lunar	

WARRANTY

Controls*	5 years
Bath & turbine* 20 years	
*Some restrictions apply I www.bainultra.com/warranty	







AYOURA 7838 (FREESTANDING) 78 x 38 x 27

ACCESSORIES - OPTIONAL

Clear acrylic grab bars


With Chrome, Brass or Brushed nickel inserts

Other


BainUltra® recommends choosing a faucet that is no higher than 4 5/8". This is the height clearance under the massage table when it is installed. If the faucet exceeds this height, it will not be possible to install the massage table.

TOTAL PRICE

\$



INCLUDING WOOD OR ACRYLIC INSERT



ACCESS PANEL FOR:

- TURBINE
- ELECTRICAL
- PLUMBING



LETTER	DESCRIPTION	MEASURE
A	Outside edge to center drain	28 5/8"
В	Outside edge to overflow	19"
С	Total length	80 3/8"
D	Total width	37 3/4"
E	Bathing well length	59 1/2"
F	Bathing well width	20 7/8"
G	Bottom bathing well length	39 5/8"
Н	Raised seat length	24 1/8"
I	Total height to headrest	27 3/16"
J	Height from bottom of tub to top deck	25 3/4"
K	Height from bottom of tub to bottom of lip	23 3/4"
L	Height from drain to center of overflow	19 1/2"
M	Maximum water level	17 3/4"
N	Slope of backrest	30°
0	Base length	63"
P	Base width	26"
Q	Plumbing zone length	16"

Indicates turbine position Indicates heated backrest

Indicates LED light position

AYOURA 7838 FREESTANDING TECHNICAL SPECIFICATIONS

Jets	63
US gallons	65
Imp. gallons	54
Approx. shipping weight	325 lbs
Turbine power	755 W
Air heater	700 W

Hot water supply required	Should be 70% of water capacity of tub or greater.
Turbine access	Included in access panel.
Standards	All BainUltra products meet and/or exceed the highest quality and certification standards. For further details about BainUltra's product standards, please go to the following link: (www.bainultra.com/standards).

Our products must be installed by certified professionals only and according to our Owner's Manual as well as federal, provincial/state and local building codes and regulations (www.bainultra.com/documentation).

1 800 463.2187 😲 | From 8 a.m. to 8 p.m. Monday to Thursday (EST) . From 8 a.m. to 5 p.m. on Friday (EST)

The specifications shown indicate the outer edge dimension and the inside bathing capacity dimension measured at air jets' height. The manufacturer accepts a 1/4" [0.64 cm] variance. There are variations on each product and specifications are subject to change as we improve upon our product as required. The dimensions needed for site preparation and structure building will differ. BainUltra® assumes no responsibility for preparatory work done prior to the product being on site.