

PRODUCT SHEET ELEGANCIA 6032

60 x 32 x 19

A bath shaped to your preferences.



_			
$^{\circ}$	BAIN	JLIK	A۳

FEATURES	
Installation type	- Drop-in - Alcove (3 walls)
No. of bathers	1
Heated backrest	1
Control	MiaPlus
ThermoMasseur® bath	\$
Soaker bath	\$

THERAPIES	
Chromatherapy 2-LED	\$
Sound Therapy (Euphonia™ System)	\$

COLO	RS				
Standa	ards				
White	Bone	Biscuit	Almond		
Option	als			\$	
Black	Mexican sand	Innocent blush	Cashmere	Sandbar	Grey

WAKKANIT	
Controls*	5 years
Bath & turbine*	20 years

*Some restrictions apply I www.bainultra.com/warranty








ELEGANCIA 6032 60 x 32 x 19


ACCESSORIES - OPTIONAL


Skirts (with C12)	Littora \$ SJ-1 \$		Elegance	\$	
Elegancia floor	Floor pattern			\$	
Drain & overflow	- Chrome - White, Biscuit, Bone - Brass - Brushed nickel, Polished nickel - Oil-rubbed bronze - Unplated * Piping is not included for this model (D14).	\$ \$ \$	*D-14 (Elegancia) N/A N/A	\$ \$ \$ \$	D-13 (Balneo) N/A


Control	MiaMulti \$
Integrated tile flange	Included (specify right or left)
Others	There is a height difference for the integrated tile flange (see drawing Detail A). Available with or without integrated tile flange (specify right or left).
TOTAL PRICE	\$

Exclusive contour









LETTER	DESCRIPTION	MEASURE
A	Outside edge to center drain	8"
В	Outside edge to overflow	2 1/4"
C	Total length	60"
D	Total width	32"
E	Bathing well length	46 3/8"
F	Bathing well width	21"
G	Deck width	3 7/8"
Н	Deck width at backrest end (widest point)	3 3/8"
ı	Height from bottom of tub to top deck	19 1/4"
J	Height from bottom of tub to top deck	19 1/4"
K	Height from bottom of tub to bottom of lip	17 3/4"
L	Tile flange height	1"
М	Height from drain to center of overflow	14 1/2"
N	Maximum water level	12 7/8"
0	Slope of backrest	30°

Indicates turbine position

■ Indicates LED light position

• Indicates control position when factory-installed

ELEGANCIA 6032 TECHNICAL SPECIFICATIONS

700 W

Jets	41
US gallons	45
Imp. gallons	37
Approx. shipping weight	125 lbs
Turbine power	755 W

Hot water supply required	Should be 70% of water capacity of tub or greater.
Turbine access	Must be at least 18" X 22" to access the pump. Must be connected to a 15 A. 120 V, 60 Hz, protected by a ground-fault circuit interrupter (GFCI) on a dedicated line.
Standards	All BainUltra products meet and/or exceed the highest quality and certification standards. For further details about BainUltra's product standards, please go to the following link: (www.bainultra.com/standards).

Our products must be installed by certified professionals only and according to our Owner's Manual as well as federal, provincial/state and local building codes and regulations (www.bainultra.com/documentation).

Air heater

1 800 463.2187 😲 | From 8 a.m. to 8 p.m. Monday to Thursday (EST) . From 8 a.m. to 5 p.m. on Friday (EST)