

MECHANICAL FAUCETS

201-AGN8AE35-317CP



Manual and Metering Faucets

Product Type

Deck Mounted 8" Fixed Centers Concealed Hot and Cold Water Sink Faucet

Features & Specifications

- 8" Fixed Centers
- 8" Rigid / Swing Gooseneck Spout
- 1.5 GPM (5.7 L/min) Aerator
- 4" Wristblade Handle
- Quaturn Compression Operating Cartridge
- 1/2" NPSM Supply Inlets and Coupling Nut for 3/8" or 1/2" Flexible Riser

Performance Specification

- Rated Operating Pressure: 20-125 PSI
- Rated Operating Temperature: 40-140°F

Warranty

- Lifetime Limited Faucet Warranty
- 5-Year Limited Cartridge Warranty
- 1-Year Limited Finish Warranty

Codes & Standards

- ASME A112.18.1/CSA B125.1
- Certified to NSF/ANSI 61, Section 9 by CSA
- ADA ANSI/ICC A117.1

Job Name _____

Item Number _____

Section/Tag _____

Model Specified _____

Architect _____

Engineer _____

Contractor _____

☐ Submitted as Shown ☐ Submitted with Variations

Date _____



2100 South Clearwater Drive
Des Plaines, IL
P: 847/803-5000
F: 847/803-5454
Technical: 800/TEC-TRUE
www.chicagofaucets.com

Architect/Engineer Specification

The technical drawing illustrates a three-arm faucet assembly. The left view shows the side profile of the faucet, featuring three curved spouts. Dimensions include a height of 4 [102] from the base to the top of the central arm, a diameter of $\phi 1-1/4$ [32] at the base of the central arm, and a total width of 8 [203]. The right view shows the top-down perspective of the faucet, highlighting the curved spout and its dimensions. Key dimensions include a horizontal reach of 8 [203], a vertical height of 7-1/2 [191] from the base to the tip of the spout, and a maximum ware thickness of 1-3/8 [35]. A note indicates the use of a 1/2 NPSM COUPLING NUT FOR 3/8 OR 1/2 FLEXIBLE RISER.

Last Revision: 07/25/2011 • Date Printed: 03/25/2013 • Product specifications subject to change without notice