

Manual and Metering Faucets

Product Type

Deck Mounted 4" Fixed Centers Hot and Cold Water Sink
Faucet

Features & Specifications

- 4" Fixed Centers
- 6" S Type Swing Spout
- Full Flow
- 2-3/8" Lever Handle
- Ceramic 1/4 Turn Operating Cartridge
- 1/2" NPSM Supply Inlets and Coupling Nut for 3/8" or 1/2" Flexible Riser

Performance Specification

- Rated Operating Pressure: 20-125 PSI
- Rated Operating Temperature: 40-140°F

Warranty

- Lifetime Limited Faucet Warranty
- 5-Year Limited Cartridge Warranty
- 1-Year Limited Finish Warranty

Codes & Standards

- ASME A112.18.1/CSA B125.1
- Certified to NSF/ANSI 61, Section 9 by CSA
- ADA ANSI/ICC A117.1

Job Name _____

Item Number _____

Section/Tag _____

Model Specified _____

Architect _____

Engineer _____

Contractor _____

☐ Submitted as Shown ☐ Submitted with Variations

Date _____



Architect/Engineer Specification

3/4 A.N. HOSE
THREAD OUTLET

2-3/8
[60]

6
[152]

4-C-C
[102]

1/16-1-1/2
[2-38]
MAXIMUM WARE
THICKNESS

6
[152]

1/4 [6]
OFFSET

3-5/8
[92]

2
[51]

2-3/8
[60]

Ø 1-3/4
[44]

1/2 NPSM COUPLING
NUT FOR 3/8 OR 1/2
FLEXIBLE RISER

Last Revision: 07/25/2011 • Date Printed: 03/25/2013 • Product specifications subject to change without notice