

MECHANICAL FAUCETS

895-317GN2BE4CP



Manual and Metering Faucets

Product Type

Deck Mounted 4" Fixed Centers Hot and Cold Water Sink Faucet

Features & Specifications

- 4" Fixed Centers
- 5-1/4" Rigid / Swing Gooseneck Spout
- 2.0 GPM (7.6 L/min) Spray
- 4" Wristblade Handle
- Quaturn Compression Operating Cartridge
- 1/2" NPSM Supply Inlets and Coupling Nut for 3/8" or 1/2" Flexible Riser

Performance Specification

- Rated Operating Pressure: 20-125 PSI
- Rated Operating Temperature: 40-140°F

Warranty

- Lifetime Limited Faucet Warranty
- 5-Year Limited Cartridge Warranty
- 1-Year Limited Finish Warranty

Codes & Standards

- ASME A112.18.1/CSA B125.1
- Certified to NSF/ANSI 61, Section 9 by CSA
- ADA ANSI/ICC A117.1

Job Name _____

Item Number _____

Section/Tag _____

Model Specified _____

Architect _____

Engineer _____

Contractor _____

☐ Submitted as Shown ☐ Submitted with Variations

Date _____



2100 South Clearwater Drive
Des Plaines, IL
P: 847/803-5000
F: 847/803-5454
Technical: 800/TEC-TRUE
www.chicagofaucets.com

Architect/Engineer Specification

Technical drawings of a 1/2 NPSM coupling nut for 3/8 or 1/2 flexible riser. The left drawing is a top view showing a central vertical riser and two side risers. Dimensions include a width of 4 [102], a height of 6 [152], and a central riser diameter of Ø 1 [25]. The right drawing is a side view showing the riser's profile, a 3° bend, a height of 5-3/8 [137], and a 1/4 [6] OFFSET. Both drawings show a 1/16-1-1/2 [2-38] WARE THICKNESS and a 2-3/8 [60] dimension at the bottom.

Last Revision: 09/12/2011 • Date Printed: 03/25/2013 • Product specifications subject to change without notice