

Manual and Metering Faucets

Product Type

Deck Mounted 4" Fixed Centers Hot and Cold Water Sink
Faucet

Features & Specifications

- 4" Fixed Centers
- 3-1/2" Flow Control Rigid / Swing Gooseneck Spout
- 1-3/4" Vandal Proof MVP Metering Push Handle
- MVP Metering Adjustable Cycle Time Closure Cartridge
- 1/2" NPSM Supply Inlets and Coupling Nut for 3/8" or 1/2" Flexible Riser
- 1.5 GPM (5.7 L/min) Laminar Flow Control Insert in Spout Inlet

Performance Specification

- Rated Operating Pressure: 20-125 PSI
- Rated Operating Temperature: 40-140°F

Warranty

- Lifetime Limited Faucet Warranty
- 5-Year Limited Cartridge Warranty
- 1-Year Limited Finish Warranty

Codes & Standards

- ASME A112.18.1/CSA B125.1
- Certified to NSF/ANSI 61, Section 9 by CSA
- ADA ANSI/ICC A117.1

Job Name _____

Item Number _____

Section/Tag _____

Model Specified _____

Architect _____

Engineer _____

Contractor _____

☐ Submitted as Shown ☐ Submitted with Variations

Date _____



Architect/Engineer Specification

13/16-24
MALE THREAD

10°

3-1/2
[89]

7-1/4
[184]

1/4 [6]
OFFSET

9-5/8
[244]

2-3/8
[60]

1/16-1-1/2
[2-38]
WARE THICKNESS

2
[51]

Ø1
[25]

Ø1-3/4
[44]

6
[152]

3-3/8
[86]

4 C-C
[102]

1/2 NPSM COUPLING
NUT FOR 3/8 OR 1/2
FLEXIBLE RISER

Last Revision: 02/09/2012 • Date Printed: 03/25/2013 • Product specifications subject to change without notice