

Extension Tubes

1 ft (0.3 m) to 15 ft (4.5 m)

Standard 1 ft (0.3 m) shown


Technical Specifications	
Model number	IS12
Number and type of airfoils	10 patented MiniTEC airfoils
Airfoil finish	Clear anodized aluminum
Winglet (standard finish)	Isis winglet (black)
Fan weight (as shown)	104 lbs (47.1 kg)
Prime mover	Gearless direct drive
Maximum speed	43 RPM
Maximum amps	3.9 A
Input power and required breaker	100–125 VAC, 60 Hz, 1 Φ , 10 A
Controller (standard color)	Isis wall switch (white)
Sound level (max speed) ¹	< 35 dBA
Minimum airfoil clearances required	10 ft (305 mm) above the floor 2 ft (610 mm) on sides 2 ft (610 mm) below ceiling deck
Certifications	ANSI/UL 507 CAN/CSA C.22.2 No. 113-08
Warranty ²	10 year warranty with factory installation

¹ Sound level measured at a blade height of 20 ft (6.1 m) and 20 ft (6.1 m) horizontally from center of fan.

² 10 year parts, lifetime airfoils and hub, 1 year labor warranty; certain exclusions may apply. See complete warranty for details.

Fan weight does not include upper mount or extension tube

Controller



Fits standard electrical box
White cover plate included
3¼" (83 mm) x 5" (130 mm)

Optional Colors*

Ask about custom color options
and other alternative finishes

Modern
White

Raven
Black

Antique
Brown

*Base model is clear
anodized aluminum

Isis Features

- Fits flat or sloped ceilings as low as 12 ft (3.7 m)
- Silent operation for quiet spaces
- Year-round energy savings
- Compact and attractive design
- Easy to use controller



Isis Options

- 8 ft (2.4 m), 10 ft (3.1 m), 12 ft (3.6 m)
- Outdoor-use models also available
- Automation interface
- Color options and custom color matches
- 200–250 VAC, 50 Hz, 1 Φ model available

Covered by one or more of the following U.S. Patents: 6,244,821; 6,589,016; 6,817,835; 6,939,108; 7,252,478; 7,284,960; D587,799; D607,988; 7,654,798; D635,237; 7,934,907; D641,075; D642,674; 8,075,273; D650,893; 8,079,823; 8,147,182; 8,147,204; 8,152,453; 8,162,613 and other patents pending.