



Technical Specifications			
Model number	IS10		
Number and type of airfoils	10 patented MiniTEC airfoils		
Airfoil finish	Clear anodized aluminum		
Winglet (standard finish)	Isis winglet (black)		
Fan weight (as shown)	103 lbs (47 kg)		
Prime mover	Gearless direct drive		
Maximum speed	60 RPM		
Maximum amps	3.9 A		
Input power and required breaker	100-125 VAC, 60 Hz, 1 ф, 10 A		
Average power usage-low/med/high speed	15 W / 43 W / 207 W		
Controller (standard color)	Isis wall switch (white)		
Sound level (max speed) ¹	< 35 dBA		
Minimum airfoil clearances required	10 ft (305 mm) above the floor 2 ft (610 mm) on sides 2 ft (610 mm) below ceiling deck		
Certifications	ANSI/UL 507 CAN/CSA C.22.2 No. 113-08		
Warranty ²	10 year warranty with factory installation		

White cover plate included 31/4" (83 mm) x 5" (130 mm)

Fits standard electrical box

4.79" (121.7 mm)

Color Options^{*}

Ask about color options and other alternative finishes



TIA.





^{*}Base model is clear anodized aluminum

Sound level measured at a blade height of 20 ft (6.1 m) and 20 ft (6.1 m) horizontally from center of fan.
² 10 year parts, lifetime airfoils and hub, 1 year labor warranty; certain exclusions may apply. See complete warranty for details

Isis Sizing Chart	Ceiling Height				
Approximate Room Size	12' (3.7 m)	17' (5.2 m)	22' (6.7 m)	27' (8.2 m)	
20' x 20' (6.1 m x 6.1 m)	8-ft (2.4 m)	8-ft (2.4 m)	8-ft (2.4 m)	9-ft (2.7 m)	
30' x 30' (9.1 m x 9.1 m)	8-ft (2.4 m)	9-ft (2.7 m)	9-ft (2.7 m)	10-ft (3.1 m)	
40' x 40' (12.2 m x 12.2 m)	8-ft (2.4 m)	9-ft (2.7 m)	10-ft (3.1 m)	10-ft (3.1 m)	

For cooling an active environment such as a gym, use the fan size indicated by the sizing chart set at high speed.

For gentle air circulation in an environment such as an office or restaurant, use the fan size indicated by the sizing chart set at a slower speed.

Isis Features

- Fits flat or sloped ceilings as low as 12 ft (3.7 m)
- Silent operation for quiet spaces
- Year-round energy savings
- Compact and attractive design
- Easy to use controller



Isis Options

- 8 ft (2.4 m), 9 ft (2.7 m), 10 ft (3.1 m)
- Outdoor-use models also available
- Automation interface
- Color options and custom color matches
- 200–250 VAC, 50 Hz, 1 Φ model available

 $Covered \ by \ one \ or \ more \ of \ the \ following \ U.S. \ Patents: \ 6,244,821; \ 6,589,016; \ 6,817,835; \ 6,939,108; \ 7,252,478; \ 7,284,960; \ 7,654,798; \ D587,799; \ D607,988 \ and \ other \ patents \ pending.$



