

Extension Tubes

1 ft (0.3 m) to 15 ft (4.5 m)

Standard 1 ft (0.3 m) shown


Technical Specifications

Model number	IS08
Number and type of airfoils	10 patented MiniTEC airfoils
Airfoil finish	Clear anodized aluminum
Winglet (standard finish)	Isis winglet (black)
Fan weight (as shown)	95 lbs (43 kg)
Prime mover	Gearless direct drive
Maximum speed	95 RPM
Maximum amps	3.9 A
Input power and required breaker	100-125 VAC, 60 Hz, 1 Φ , 10 A
Average power usage—low/med/high speed	11 W / 47 W / 290 W
Controller (standard color)	Isis wall switch (white)
Sound level (max speed) ¹	< 35 dBA
Minimum airfoil clearances required	10 ft (305 mm) above the floor 2 ft (610 mm) on sides 2 ft (610 mm) below ceiling deck
Certifications	ANSI/UL 507 CAN/CSA C.22.2 No. 113-08
Warranty ²	10 year warranty with factory installation

¹Sound level measured at a blade height of 20 ft (6.1 m) and 20 ft (6.1 m) horizontally from center of fan.

²10 year parts, lifetime airfoils and hub, 1 year labor warranty; certain exclusions may apply. See complete warranty for details.


Controller



Fits standard electrical box
White cover plate included
3 1/4" (83 mm) x 5" (130 mm)

Color Options*

Ask about color options
and other alternative finishes



*Base model is clear
anodized aluminum

Isis Sizing Chart

Approximate Room Size	Ceiling Height			
	12' (3.7 m)	17' (5.2 m)	22' (6.7 m)	27' (8.2 m)
20' x 20' (6.1 m x 6.1 m)	8-ft (2.4 m)	8-ft (2.4 m)	8-ft (2.4 m)	9-ft (2.7 m)
30' x 30' (9.1 m x 9.1 m)	8-ft (2.4 m)	9-ft (2.7 m)	9-ft (2.7 m)	10-ft (3.1 m)
40' x 40' (12.2 m x 12.2 m)	8-ft (2.4 m)	9-ft (2.7 m)	10-ft (3.1 m)	10-ft (3.1 m)

For cooling an active environment such as a gym, use the fan size indicated by the sizing chart set at high speed.

For gentle air circulation in an environment such as an office or restaurant, use the fan size indicated by the sizing chart set at a slower speed.

Isis Features

- Fits flat or sloped ceilings as low as 12 ft (3.7 m)
- Silent operation for quiet spaces
- Year-round energy savings
- Compact and attractive design
- Easy to use controller



Isis Options

- 8 ft (2.4 m), 9 ft (2.7 m), 10 ft (3.1 m)
- Outdoor-use models also available
- Automation interface
- Color options and custom color matches
- 200–250 VAC, 50 Hz, 1 Φ model available

Covered by one or more of the following U.S. Patents: 6,244,821; 6,589,016; 6,817,835; 6,939,108; 7,252,478; 7,284,960; 7,654,798; D587,799; D607,988 and other patents pending.

