



80 Nottingham Dr
Nottingham, PA 19362
p. 888.397.2656
f. 610.932.4386
www.zandur.com

PRODUCT SPECIFICATIONS #Z532

SOLID CORK FLOORING

Available Finishes: Polyurethane, Unfinished, Carnauba Wax

Tile Dimension: All Product is shipped in nominal dimensions unless specified otherwise.

Nominal Size	Actual Size	Metric Units	ft ² per tile
12" X 12"	11.81" X 11.81"	300mm X 300mm	0.97
12" X 24"	11.81" X 23.62"	300mm X 600mm	1.94
12" X 36"	11.81" X 35.43"	300mm X 900mm	2.91
24" X 24"	23.62" X 23.62"	600mm X 600mm	3.88

Thickness: 3/16" (4.8mm), 5/16" (8.0mm), 1/2" (12.7mm)

Test Data:

Test Description	Standard	Result	Meets or exceeds Standard
Smoke Density	ASTM E662	<340	Y
Fire Resistance	ASTM E648	Class II	Y
Static Load Limit	ASTM F970-00	.020" @650 lbs after 24 hrs	
Sound Transmission Loss	ASTM E90-02	STC = 54 dB	
Impact Sound Transmission	ASTM E92-90	IIC = 51 dB	
Coefficient of Friction	ASTM D2047	.98 Dry; 1.20+ Wet	Y - Meets ADA Recommendations
Chemical Resistance		Excellent Resistance - Details available upon request	
Cork Flooring Standard	ISO3810	Meets European Cork Floor Standard	Y

Test results may vary from tile to tile due to natural content of product.