SINGLE CIRCUIT POWER AND DATA SYSTEMS

MODESTY PANEL:

- Back panel is extruded in aluminum, with 3 separate channels: one for the power and two for running data wires.
- Front door panel is 18Gauge formed cold-rolled perforated steel.
- Door is hinged at the bottom; secured with spring steel push pins.
- Optional locking door available

POWER:

- 15 Amp, single-circuit, plug-in, interconnected power modules
- Each system has an integrated circuit breaker and a surge protector.
- Powered Form Modesty units up to 48" long have one set of simplex plugs (2 plugs) as a standard. Units longer than 48" and up to 96" long have two sets of plugs (4 plugs) as standard.
- ETL Listed to UL962 Powered Table Systems)
- Maximum of 16 simplex outlets per circuit. This can be accomplished in various configurations of units (some can have 2 plugs, others 4, etc.)
- Capable of being powered from the right or the left.
- 9ft power cord on the 1st unit. Custom lengths up to 15' available.
- System is designed to conform with UL962, with keyed connectors that prevent the system from being hooked up in numerical order (1-2-3-4-5-6, etc.).
- Endcaps are available for the units.

DATA:

- One set of (2) RJ45 jacks provided as a standard on units up to 48". Two sets (4) jacks provided on units from 48" to 96."
- One jack per set is a CAT6 (data). The other is a CAT3 (voice).
- Systimax jacks are standard. Superior UMJ jacks are available as a standard option. Alternative configurations and jack types are available...samples must be submitted for approval.
- Jacks can be ordered already wired, with various configurations of termination on the other end (male or female connections, etc.).













