



filzfelt

Roll Cut Design Felt

Roll Cut Design Felt



A bolt of 100% Wool Design Felt may be sliced into full length strips that can vary in width. Only full bolts of Roll Cut Design Felt may be purchased and please note that lengths are not finished cuts.

Standard Colors



2mm



3mm



5mm

Specifications

Content	100% Wool Design Felt
Felt Thickness	2 mm (1/16 in), 3 mm (1/8 in), 5 mm (3/16 in), 8 mm (5/16 in) or 10 mm (3/8 in)
Minimum	1 bolt
Maximum Length	2mm, 3mm or 5mm: 69 in (175 cm) x 75 ft (22 m) 8mm or 10mm: 60 in (155 cm) x 50 ft (15 m)
Approx. Bolt Length	2mm, 3mm or 5mm: 24 lin yd (20 lin m) 8mm or 10mm: 17 lin yd (15 lin m)
Maintenance	Vacuum occasionally to remove general air-borne debris. Should soiling occur, clean with a mild, water-free dry cleaning solvent.
Durability	Contract or residential
Colorfastness to Light	Class 4-5 (40 hours)
Colorfastness to Crocking	Class 3-4 (wet), Class 4-5 (dry)
Environmental	Oeko-Tex Standard 100 Certified Product Class II
Flammability	ASTM E84 Class A (unadhered) Euroclass EN13501-1: B-s1-d0 (flame treated), D-s1-d0 (untreated)
Standard Colors	2mm: 100, 110, 124, 150, 160, 170, 173, 175, 179, 200, 201, 209, 231, 242, 250, 255, 265, 269, 272, 282, 284, 286, 300, 308, 343, 377, 378, 384, 423, 425, 426, 476, 497 3mm: 100, 102, 105, 110, 116, 124, 125, 131, 136, 150, 151, 156, 160, 170, 173, 175, 179, 180, 200, 201, 203, 209, 220, 231, 242, 250, 255, 265, 269, 272, 274, 282, 284, 286, 300, 308, 312, 319, 331, 343, 377, 378, 384, 385, 408, 415, 423, 425, 426, 437, 448, 467, 476, 497, 503, 534, 540, 548, 613, 626, 686, 713, 732 5mm: 100, 102, 105, 110, 150, 160, 170, 173, 175, 179, 180, 200, 201, 209, 220, 242, 250, 272, 274, 282, 284, 286, 300, 308, 312, 319, 331, 343, 377, 378, 384, 385, 408, 415, 423, 425, 426, 437, 448, 503, 540, 613, 713 8mm: 200 10mm: 200