




M1R1 / M1R2





M10-xxx-xx-SF1/2




M10-xxx-xx-SG




M1RA1 / M1RA2




M1S1 / M1S2



M150-xxx-xx-SF1/2



M150-xxx-xx-SG



M1SA1 / M1SA2



For specifications, see appropriate spec sheet:

(CLICK HERE for M100 Recessed)

(CLICK HERE for M100 Semi-Recessed)

### Ordering Matrix

#### M100 Linear Fluorescent Recessed & M100 Linear Fluorescent Semi-Recessed

**Series<sup>1</sup>** | **M1R1** M100 Recessed (Continuous Flange) | **M1R2** M100 Recessed (Flangeless Endcaps) | **M10** M100 Recessed (Flangeless Extrusion) |  
**M1S1** M100 Semi-Recessed (Continuous Flange) | **M1S2** M100 Semi-Recessed (Flangeless Endcaps) | **M150** M100 Semi-Recessed (Flangeless Extrusion) |  
**M1RA1/M1RA2/M1A** M100 Recessed (asymmetrical configurations) || **M1SA1/M1SA2/M150** M100 Semi-Recessed (asymmetrical configurations)

**Lamping** | **1T5** F28T5 | **2T5** (2x)F28/T5 | **1T5HO** F54T5HO | **1T8** F032/T8

**Shielding** | **SA** Specular Parabolic | **MA** Matte Parabolic | **MP** Silky Specular | **PL** Matte Perforated Parabolic | **SD** Satine Lens |  
**OD** Extra Diffuse Lens<sup>5</sup> | **AMP** Asymmetrical Louver

**Mounting<sup>2</sup>** | **SH** Suspension Clips | **RC** Rotating Crossbars | **R** 1/4 - 20 Rod | **PM** Perimeter Mount | **TS** 1" Studs (factory installed) |  
**SG** or **SG1** Slot Grid Recessed or Semi-Recessed | **SF<sub>x</sub>** Spackle Flange | **DC** Ceiling Panels up to 2" thick

**Lengths (nominal)<sup>3</sup>** | **004** 4 foot | **008** 8 foot | **012** 12 foot

**Finish** | **WH** White | **BK** Black | **SV** Silver | **SP** Specify RAL#

**Voltage** | **120** | **277** | **347**

**Options<sup>4</sup>** | **TB** T-Bar Ceiling Systems | **EM** Stand-by Battery Pack | **DMA** Digital Addressable Dimming (consult factory) | **DM** Dimming | **FS** Single Fusing |  
**SI** Satine Acrylic Inlay | **FW** Flex Whip | **FW1** Flex Whip (dimming) | **CCEA** Chicago Plenum | **TRACK** (Eutrac 2-C Standard) | **MR16 DOWNLIGHTS** (see spec sheet)

<sup>1</sup> Add "S" to Series numbers to designate staggered lamps versions. <sup>2</sup> Consult website spec sheets for mounting configuration details. <sup>3</sup> For other lengths/configurations or continuous runs, indicate nominal length rounded to the next highest foot using three digits. Factory will supply layout drawings. Individual fixtures cannot be field joined. <sup>4</sup> Not all options available with all systems, see website spec sheet for more details.

<sup>5</sup> OD - Extra Diffuse Lens is recommended for staggered lamps versions.

#### Staggered Lamps

Add an "S" to a Series number to designate it to be a "staggered lamps" configuration for complete elimination of socket shadows (use shielding OD - Extra Diffuse Lens).  
 Examples: **M1R1S** & **M1S1S**

