


M60

Linear Fluorescent
Recessed

se'lux®



Project: _____ Type: _____ Qty: _____

Fixture Series _____ Lamp Type _____ Shielding _____ Mounting _____ Linear Footage _____ Finish _____ Voltage _____

Options (refer to separate data sheets for ordering codes and details)

Fixture Series	Lamp Type	Shielding	Mounting	Linear Footage	Finish	Voltage	Options
M6R1 M60 Recessed Continuous Flange (Flanged Extrusion/ Flanged Endcaps)	1T5 F28T5 1T5HO F54T5HO	MA Matte Parabolic MP Silky Specular Parabolic Louver SD Satine Lens OD Extra Diffuse Lens	SH Suspension Clips RC Rotating Crossbars PM Perimeter Mount TS 1" Studs (factory installed)	004 4 foot 008 8 foot 012 12 foot For actual lengths see layout dimensions. For other lengths, configurations indicate nominal length rounded to the next highest foot. Factory will supply layout drawings. Individual fixtures cannot be field joined.	WH White BK Black SV Silver SP Specify RAL#	120 277 347	TB Lengths to Fit 2' Grid T-Bar Ceiling System (M6R1 only) (qty.)EM Stand-by Battery Pack ¹ (prefix quantity, i.e. - 5EM) FS Single Fusing DM Dimming ¹ (specify system) DMA Digital Addressable Dimming ¹ SI Satine Acrylic Inlay ² FW Flex Whip (standard) FW1 Flex Whip (dimming) Track Eutrac Standard ³ DL Suitable for Damp Locations CCEA Chicago Plenum Downlights (See MR11 spec sheet, pp.98)


¹Must be low profile ballasts (1 3/8" wide x 1 3/8" high); consult factory for details.

²Available for MP Louver only.


³Consult factory for details.

Mounting Diagrams


Suspension Clips (SH)




Pre-installed Rod (TS)



Rotating Crossbars (RC)





Perimeter Mount (PM)



Scale = 1 : 8

Track

Track insert including track available for all configurations, consult factory for details.



Scale = 1 : 4

1. Housing - Continuous, 6063-T5 extruded aluminum profile up to 16 feet long.

2. Ballast - Electronic, high power factor, class "P", type "A" sound rating. Specify 120v, 277v, or 347v. Ballast is factory pre-wired with leads to one end of fixture. Consult factory for ballast options.

3. Gear Tray - Die formed tray with specular aluminum reflector. Gear tray installs as complete electrical unit and is held in place with 1/4 turn latches. It is fully accessible from below ceiling.

4. Flange - 5/16" (8mm) wide flange is part of the main extruded body. Specify continuous flange (M6R1) or flush end (M6R2).

5. Lamps - As noted (by others). Other lamp lengths or wattages available, consult factory.

6. Shielding - Louvers offer excellent glare control in longitudinal, lateral, and all diagonal planes. High quality aluminum louvers and acrylic shielding allow true freedom of layout for today's modern spaces.

7. Spring steel suspension clips - Supplied two places, located nominally every 4 ft. Support wires Supplied and installed by others.

8. Pre-installed 1" 1/4-20 Stud - Attached to fixture every nominal 4 feet.

9. Coupling and Threaded Rod to Structure - Supplied and installed by others.

10 Rotating Crossbar - For inaccessible ceilings, adjustable for ceiling thicknesses from 1/4" to 2". Support required nominally every 4'.

11. Steel Wall Bracket and 1/4-20 Rod - Supplied nominally every 4 ft. (Fasteners to wall and wall anchors by others.)

12. Aluminum Wall Bracket - Secured to wall (fasteners and wall anchors by others) and runs entire length of fixture. Also supplied for width of M6R1 continuous flange fixtures. Allows for 1/8" gap between flange and wall to create shadow line.

Interior Luminaire Finish - Standard interior colors are White (WH), Black (BK) and Silver (SV). RAL Classic colors (SP) are available, please specify RAL#.

SELUX Corp. © 2006
TEL: (845) 691-7723
FAX: (845) 691-6749
www.selux.com/usa
M6R-01 (v5.0)



Union Made Affiliated
with IBEW Local 363


In a continuing effort to offer the best product possible, we reserve the right to change, without notice, specifications or materials that in our opinion will not alter the function of the product. Specification sheets found at www.selux.com/usa are the most recent versions and supercede all other printed or electronic versions.

M6R1 and M6R2 Standard Layout Dimensions

M6R1 Recessed - nominal 4 foot individual




M6R1 Recessed - T-Bar Length - nominal 4 foot individual



M6R1 Recessed - nominal 8 foot individual




M6R1 Recessed - T-Bar Length - nominal 8 foot individual




M6R1 Recessed - nominal 12 foot individual



M6R1 Recessed - T-Bar Length - nominal 12 foot individual



Typical Side View



Suspensions supplied spaced nominally every 4 feet.

Fixture supplied with 7/8 knockout located 2 1/8" from end in top of fixture.

	T5 (1 or 2 lamp)			
	M6R1/M6R2 Including Endplates	M6R1 Outside Flange	M6R1/M6R2 - TB Including Endplates	M6R1 - TB Outside Flange
4 foot individual	46.63" (1184mm)	47.28" (1201mm)	47.22" (1199mm)	47.91" (1216mm)
8 foot individual	93.03" (2363mm)	93.72" (2380mm)	95.22" (2419mm)	95.91" (2436mm)
12 foot individual	139.44" (3542mm)	140.13" (3559mm)	143.22" (3638mm)	143.91" (3655mm)

For other lengths, lamping, continuous runs or configurations please specify overall length (in feet), accessories desired and sketch/drawing of configuration. SELUX will detail project drawings upon order and supply submittal drawings for approval. Individual fixtures cannot be field joined. If you have any questions please contact SELUX customer service or applications engineering for assistance (1-800-SELUX-CS).

Continuous Flange (M6R1)



Flush End (M6R2)

