

M60

Recessed Linear Fluorescent
Slot Grid / Thick Ceiling Panel

se'lux®



Project: _____ **Type:** _____ **Qty:** _____

M60	—	—	—	—	—	—	—
Fixture Series	Lamp Type	Shielding	Mounting	Nominal Length	Finish	Voltage	
—	—	—	—	—	—	—	—

Options (refer to separate data sheets for ordering codes and details)


Fixture Series	Lamp Type	Shielding	Mounting	Nominal Length	Finish	Voltage	Options
M60 M60 Recessed Multi-Mount Form	1T5 F28T5 1T5HO F54T5HO	MA Matte Parabolic MP Silky Specular Parabolic Louver SD Satine Lens OD Extra Diffuse Lens	SG Slot Grid DC Ceiling Panels up to 2" thick (lengths per submittal drawings)	004 4 foot 008 8 foot 012 12 foot For actual lengths see following page. For other lengths, configura- tions indicate nominal length rounded to the next highest foot. Factory will supply layout draw- ings. Individual fixtures cannot be field joined.	WH White BK Black SV Silver SP Specify RAL#	120 277 347	TB Lengths to Fit 2' Grid T-Bar Ceiling System (qty.) EM Stand-by Battery Pack ¹ (prefix quantity, i.e. - 5EM) FS Single Fusing DM Dimming ¹ (specify system) DMA Digital Addressable Dimming ¹ SI Satine Acrylic Inlay ² FW Flex Whip (standard) FW1 Flex Whip (dimming) Track Eutrac Standard ³ DL Suitable for Damp Locations CCEA Chicago Plenum Downlights (See MR11 spec sheet, pp.98)

¹Must be low profile ballasts (1 1/8" W x 1 3/16" H); consult factory for details.

²Available for MP Louver only.

³Consult factory for details.

Slot Grid (SG)



1. Housing - Continuous, 6063-T5 extruded aluminum profile up to 16 feet long.

2. Ballast - Electronic, high power factor, class "P", type "A" sound rating. Specify 120v, 277v, or 347v. Ballast is factory pre-wired with leads to one end of fixture. Consult factory for ballast options.

3. Gear Tray - Extruded aluminum, with white painted finish. Gear tray installed as a complete electrical unit and is held in place with knurled dress nuts. It is fully accessible from below ceiling.

4. Lamps - As noted (by others). Other lamp lengths or wattages available, consult factory.

5. Shielding - Louvers offer excellent glare control in longitudinal, lateral, and all diagonal planes. High quality aluminum louvers and acrylic shielding allow true freedom of layout for today's modern spaces.

6. Support Wire to Structure - Supplied and installed by others.

7. Support Bracket - Supplied nominally every four feet.

8. Slot Grid Beam and Cross Tees - Supplied and installed by others.

9. Pre-installed 1" 1/4-20 Stud - Attached to fixture every nominal 4 feet.


10. Coupling and Threaded Rod to Structure - Supplied and installed by others.

11. Aluminum Angle Brackets - Run entire length of fixture to block view into plenum area from below fixture.

12. Ceiling Panels up to 2" Thick - Supplied and installed by others. Suitable for Decoustic® ceiling panel installations. Other ceiling systems possible, please consult factory. Decoustic® is a registered trademark of Decoustics Ltd. Corporation.

Interior Luminaire Finish - Standard interior colors are White (WH), Black (BK) and Silver (SV). RAL Classic colors (SP) are available, please specify RAL#.

Ceiling Panels up to 2" thick (DC)



Union Made Affiliated
with IBEW Local 363


SELUX Corp. © 2006
TEL: (845) 691-7723
FAX: (845) 691-6749
www.selux.com/usa
M60_SG-01 (v5.0)

In a continuing effort to offer the best product possible, we reserve the right to change, without notice, specifications or materials that in our opinion will not alter the function of the product. Specification sheets found at www.selux.com/usa are the most recent versions and supersede all other printed or electronic versions.


M60 Slot Grid Layout Dimensions

Nominal 4 foot Individual


Side View



Bottom View




Typical End View (all lengths)




Nominal 8 foot Individual

Side View




Bottom View




Nominal 12 foot Individual

Side View



Bottom View



Fixture supplied with 7/8 knockout located 2 1/4" from end in top of fixture.

For other lengths, lamping, continuous runs or configurations please specify overall length (in feet), accessories desired and sketch/drawing of configuration. SELUX will detail project drawings upon order and supply submittal drawings for approval. Individual fixtures cannot be field joined. If you have any questions please contact SELUX customer service or applications engineering for assistance (1-800-SELUX-CS).