SAFETY DATA SHEET PROSOCO, Inc.



Issue Date 11-Nov-2014 Revision Date 11-Nov-2014 Version 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name Consolideck® SingleStep®

Other means of identification

Product Code 46031 UN/ID No UN1866

Recommended use of the chemical and restrictions on use

Recommended Use Restricted to professional users.
Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address PROSOCO, Inc. 3741 Greenway Circle Lawrence, Kansas 66046

Emergency telephone number

8:00 AM – 5:00 PM CST Monday-Friday 785-865-4200 **NON-BUSINESS HOURS (INFOTRAC)** 800-535-5053

2. HAZARDS IDENTIFICATION

Classification

Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Reproductive toxicity	Category 1B
Flammable liquids	Category 3

Label elements

Emergency Overview

Danger

Hazard statements Harmful if inhaled

Causes skin irritation
May cause genetic defects

May cause cancer

May damage fertility or the unborn child

Flammable liquid and vapor



Appearance clear Physical state Liquid Odor Aromatic

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Wash face, hands and any exposed skin thoroughly after handling

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/ .? /equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention If skin irritation occurs: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

- · May be harmful if swallowed
- · May be harmful in contact with skin

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%	Trade Secret
Xylene	1330-20-7	40 - 70	*
Ethylbenzene	100-41-4	10 - 30	*
Solvent Naptha (petroleum) light aromatic	64742-95-6	5 - 10	*
Triethoxyoctysilane	2943-75-1	1 - 5	*
1,2,4-trimethylbenzene	95-63-6	1 - 5	*
dibutyl phthalate	84-74-2	1 - 5	*

Toluene	108-88-3	0.1 - 1	*

^{*} The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures

General advice In case of accident or unwellness, seek medical advice immediately (show directions for

use or safety data sheet if possible).

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Keep eye wide open while rinsing. Call a physician

immediately. If symptoms persist, call a physician.

Skin Contact Wash off immediately with plenty of water. Wash contaminated clothing before reuse. If skin

irritation persists, call a physician. Immediate medical attention is not required.

Inhalation Move to fresh air in case of accidental inhalation of vapors or decomposition products. If not

breathing, give artificial respiration. Avoid direct contact with skin. Use barrier to give

mouth-to-mouth resuscitation. Immediate medical attention is required.

Ingestion Call a physician or poison control center immediately. Do NOT induce vomiting. Clean

mouth with water and drink afterwards plenty of water. Never give anything by mouth to an

unconscious person.

Self-protection of the first aider Remove all sources of ignition. Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Symptoms Irritating to eyes and skin. Harmful if inhaled.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use. Dry chemical. Carbon dioxide (CO2). Foam. Water spray (fog).

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Keep product and empty container away from heat and sources of ignition. Risk of ignition.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate

ventilation, especially in confined areas. Use personal protective equipment as required. Keep people away from and upwind of spill/leak. Pay attention to flashback. Take

precautionary measures against static discharges.

Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do

not flush into surface water or sanitary sewer system. See Section 12 for additional

ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so. Dike far ahead of liquid spill for later

disposal.

Methods for cleaning up Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled

containers. Take precautionary measures against static discharges. Ground and bond

containers when transferring material. Use only non-sparking tools.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks,

flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be

grounded. Use personal protective equipment as required. Do not breathe

dust/fume/gas/mist/vapors/spray.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a cool, well-ventilated place. Keep in properly labeled

containers. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot

lights, electric motors and static electricity).

Incompatible materials Strong oxidizing agents. Acids. Halogens.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Xylene 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m³	-
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m³ STEL: 125 ppm STEL: 545 mg/m³
1,2,4-trimethylbenzene 95-63-6	-	-	TWA: 25 ppm TWA: 125 mg/m³

dibutyl phthalate	TWA: 5 mg/m ³	TWA: 5 mg/m³	IDLH: 4000 mg/m³
84-74-2		(vacated) TWA: 5 mg/m³	TWA: 5 mg/m³
Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m³ Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m³ STEL: 150 ppm STEL: 560 mg/m³

NIOSH IDLH Immediately Dangerous to Life or Health

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 Other Information

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations

Ventilation systems. Ground/bond container and receiving equipment.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Wear protective gloves and protective clothing. Skin and body protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved Respiratory protection

> respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

General Hygiene Considerations When using do not eat, drink or smoke. Regular cleaning of equipment, work area and

clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Liquid Physical state **Appearance** clear Odor Aromatic

Color colorless Odor threshold No information available

Values Remarks • Method **Property** Not Applicable

Not Applicable pН

Melting point/freezing point No information available No information available Boiling point/boiling range

Flash point 41 °C / 105 °F Tag Closed Cup

Evaporation rate No information available

Flammability (solid, gas) No information available Flammability Limits in Air

Upper flammability limits No information available Lower flammability limit No information available Vapor pressure No information available

Vapor density No information available **Specific Gravity** 0.92 @ 20C Insoluble in water

Water solubility No information available Solubility in other solvents No information available **Partition coefficient** No information available **Autoignition temperature**

Decomposition temperature Kinematic viscosity Dynamic viscosity No information available No information available No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents. Acids. Halogens.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information Avoid contact with skin, eyes and inhalation of vapors Harmful by inhalation Irritating to

eyes, skin and respiratory tract

Inhalation Harmful by inhalation.

Eye contact May cause irritation.

Skin Contact Causes skin irritation.

Ingestion Do not taste or swallow. Harmful if swallowed.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Xylene 1330-20-7	= 4300 mg/kg (Rat)	> 1700 mg/kg (Rabbit)	= 5000 ppm (Rat) 4 h = 47635 mg/L (Rat) 4 h
Ethylbenzene 100-41-4	= 3500 mg/kg (Rat)	= 15354 mg/kg (Rabbit)	= 17.2 mg/L (Rat) 4 h
Solvent Naptha (petroleum) light aromatic 64742-95-6	= 8400 mg/kg(Rat)	> 2000 mg/kg(Rabbit)	> 5.2 mg/L (Rat) 4 h = 3400 ppm (Rat) 4 h
Triethoxyoctysilane 2943-75-1	= 10060 μL/kg(Rat)	= 5910 μL/kg (Rabbit)	-
1,2,4-trimethylbenzene 95-63-6	= 3400 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m³ (Rat) 4 h
dibutyl phthalate 84-74-2	= 6300 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 15.68 mg/L (Rat)4 h
Toluene 108-88-3	= 636 mg/kg (Rat)	= 8390 mg/kg (Rabbit) = 12124 mg/kg (Rat)	= 12.5 mg/L (Rat) 4 h > 26700 ppm (Rat) 1 h

Information on toxicological effects

Symptoms Irritating to eyes, respiratory system and skin. Harmful if inhaled.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

SensitizationNo information available. **Germ cell mutagenicity**No information available.

Carcinogenicity This product contains one or more substances which are classified by IARC as

carcinogenic to humans (Group I), probably carcinogenic to humans (Group 2A) or possibly

carcinogenic to humans (Group 2B).

Chemical Name	ACGIH	IARC	NTP	OSHA
Xylene 1330-20-7	-	Group 3	-	-
Ethylbenzene 100-41-4	A3	Group 2B	-	Х
Toluene 108-88-3	-	Group 3	-	-

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Not classifiable as a human carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity
STOT - single exposure
STOT - repeated exposure
No information available.
No information available.

Chronic toxicity Avoid repeated exposure. May cause adverse effects on the bone marrow and

blood-forming system.

Target Organ Effects blood, central nervous system, Eyes, Gastrointestinal tract (GI), Respiratory system, Skin.

Aspiration hazard No information available.

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 4108 mg/kg ATEmix (dermal) 2114 mg/kg mg/l

ATEmix (inhalation-dust/mist) 1.6 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
			microorganisms	

Xylene 1330-20-7	-	13.4: 96 h Pimephales promelas mg/L LC50 flow-through 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through 19: 96 h Lepomis macrochirus mg/L LC50 7.711 - 9.591: 96 h Lepomis macrochirus mg/L LC50 static 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 780: 96 h	-	3.82: 48 h water flea mg/L EC50 0.6: 48 h Gammarus lacustris mg/L LC50
		Cyprinus carpio mg/L LC50 semi-static 780: 96 h Cyprinus carpio mg/L LC50 30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static		
Ethylbenzene 100-41-4	4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static 1.7 - 3.6: 95 h Pseudokirchneriella subcapitata mg/L EC50 static	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 32: 96 h Lepomis macrochirus mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static 9.6: 96 h Poecilia reticulata mg/L LC50 static	-	1.8 - 2.4: 48 h Daphnia magna mg/L EC50
Solvent Naptha (petroleum) light aromatic 64742-95-6	-	9.22: 96 h Oncorhynchus mykiss mg/L LC50	-	6.14: 48 h Daphnia magna mg/L EC50
1,2,4-trimethylbenzene 95-63-6	-	7.19 - 8.28: 96 h Pimephales promelas mg/L LC50 flow-through	-	6.14: 48 h Daphnia magna mg/L EC50
dibutyl phthalate 84-74-2	1.2: 72 h Desmodesmus subspicatus mg/L EC50 0.4: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	0.71 - 1.2: 96 h Pimephales promelas mg/L LC50 flow-through 0.31 - 5.45: 96 h Pimephales promelas mg/L LC50 static 1.24: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 1.24 - 5.3: 96 h Oncorhynchus mykiss mg/L LC50 static 1.38 - 1.74: 96 h Lepomis macrochirus mg/L LC50 flow-through 0.42 - 1.28: 96 h Lepomis macrochirus mg/L LC50 static LC50 static	-	2.99: 48 h Daphnia magna mg/L EC50 Static 3.4: 48 h Daphnia magna mg/L EC50

Toluene	433: 96 h	15.22 - 19.05: 96 h	-	5.46 - 9.83: 48 h Daphnia
108-88-3	Pseudokirchneriella	Pimephales promelas mg/L		magna mg/L EC50 Static
	subcapitata mg/L EC50	LC50 flow-through 12.6: 96 h		11.5: 48 h Daphnia magna
	12.5: 72 h	Pimephales promelas mg/L		mg/L EC50
	Pseudokirchneriella	LC50 static 5.89 - 7.81: 96 h		3
	subcapitata mg/L EC50	Oncorhynchus mykiss mg/L		
	static	LC50 flow-through 14.1 -		
		17.16: 96 h Oncorhynchus		
		mykiss mg/L LC50 static 5.8:		
		96 h Oncorhynchus mykiss		
		mg/L LC50 semi-static 11.0 -		
		15.0: 96 h Lepomis		
		macrochirus mg/L LC50		
		static 54: 96 h Oryzias		
		latipes mg/L LC50 static		
		28.2: 96 h Poecilia reticulata		
		mg/L LC50 semi-static 50.87		
		- 70.34: 96 h Poecilia		
		reticulata mg/L LC50 static		

Persistence and degradability No information available.

Bioaccumulation

No information available.

Chemical Name	Partition coefficient
Xylene 1330-20-7	3.15
Ethylbenzene 100-41-4	3.118
1,2,4-trimethylbenzene 95-63-6	3.63
dibutyl phthalate 84-74-2	5.38
Toluene 108-88-3	2.65

No information available Other adverse effects

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Do not reuse container. Contaminated packaging

D001 U069 **US EPA Waste Number**

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
dibutyl phthalate	U069	-	-	U069
84-74-2				

This product contains one or more substances that are listed with the State of California as a hazardous waste.

DOT Not regulated (If shipped in NON BULK packaging by ground transport)

UN/ID No UN1866
Proper shipping name Resin Solution

Hazard Class 3
Packing Group III

IATA

UN/ID No UN1866
Proper shipping name Resin Solution

Hazard Class 3
Packing Group III

IMDG

UN/ID No UN1866
Proper shipping name Resin Solution

Hazard Class 3
Packing Group III

15. REGULATORY INFORMATION

International Inventories

TSCA Complies DSL/NDSL Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Xylene - 1330-20-7	1330-20-7	40 - 70	1.0
Ethylbenzene - 100-41-4	100-41-4	10 - 30	0.1
1,2,4-trimethylbenzene - 95-63-6	95-63-6	1 - 5	1.0
dibutyl phthalate - 84-74-2	84-74-2	1 - 5	1.0

SARA 311/312 Hazard Categories

Acute health hazard Yes
Chronic Health Hazard Yes
Fire hazard Yes
Sudden release of pressure hazard No
Reactive Hazard No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
---------------	--------------------------------	------------------------	---------------------------	-------------------------------

Xylene 1330-20-7	100 lb	-	-	X
Ethylbenzene 100-41-4	1000 lb	Х	X	X
dibutyl phthalate 84-74-2	10 lb	Х	X	X
Toluene 108-88-3	1000 lb	Х	X	X

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Xylene	100 lb	-	RQ 100 lb final RQ
1330-20-7			RQ 45.4 kg final RQ
Ethylbenzene	1000 lb	-	RQ 1000 lb final RQ
100-41-4			RQ 454 kg final RQ
dibutyl phthalate	10 lb	-	RQ 10 lb final RQ
84-74-2			RQ 4.54 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Ethylbenzene - 100-41-4	Carcinogen
dibutyl phthalate - 84-74-2	Developmental Female Reproductive Male Reproductive
Toluene - 108-88-3	Developmental Female Reproductive
Cumene - 98-82-8	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Xylene 1330-20-7	X	X	Х
Ethylbenzene 100-41-4	X	X	Х
1,2,4-trimethylbenzene 95-63-6	X	X	Х
dibutyl phthalate 84-74-2	X	X	Х
Toluene 108-88-3	X	X	Х

16. OTHER INFORMATION

NFPA Health hazards 2 Flammability 2 Instability 0 Physical and Chemical Properties -

HMIS Health hazards 2* Flammability 2 Physical hazards 0 Personal protection X

Prepared By
Issue Date
Revision Date
Regulatory Department
11-Nov-2014
11-Nov-2014

No information available

Revision Note

Disclaimer

The information contained on the Material Safety Data Sheet has been compiled from data considered accurate. This data is believed to be reliable, but it must be pointed out that values for certain properties are known to vary from source to source. PROSOCO, Inc. expressly disclaims any warranty express or implied as well as any liability for any injury or loss arising from the use of this information or the materials described. This data is not to be construed as absolutely complete since additional data may be desirable when particular conditions or circumstances exist. It is the responsibility of the user to determine the best precautions necessary for the safe handling and use of this product for his unique application. This data relates only to the specific material designated and is not to be used in combination with any other material. Many federal and state regulations pertain directly or indirectly to the product's end use and disposal of containers and unused material. It is the purchaser's responsibility to familiarize himself with all applicable regulations.

End of Safety Data Sheet