

# SAFETY DATA SHEET

## PROSOCO, Inc.



Issue Date 07-Nov-2014

Revision Date 07-Nov-2014

Version 1

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

#### Product identifier

**Product Name** Stand Off® SLX100® Water & Oil Repellent <350 g/L

#### Other means of identification

**Product Code** 55035

**UN/ID No** UN1866

#### Recommended use of the chemical and restrictions on use

**Recommended Use** Water repellent.

**Uses advised against** No information available

#### Details of the supplier of the safety data sheet

##### **Manufacturer Address**

PROSOCO, Inc.  
3741 Greenway Circle  
Lawrence, Kansas 66046

#### Emergency telephone number

**8:00 AM – 5:00 PM CST Monday-Friday**

785-865-4200

**NON-BUSINESS HOURS (INFOTRAC)**

800-535-5053

### 2. HAZARDS IDENTIFICATION

#### Classification

Acute toxicity - Oral	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Specific target organ toxicity (single exposure)	Category 2
Flammable liquids	Category 3

#### Label elements

#### **Emergency Overview**

##### **Warning**

##### **Hazard statements**

Harmful if swallowed

Harmful if inhaled

Causes skin irritation

Causes serious eye irritation

May cause damage to organs

Flammable liquid and vapor



**Appearance** clear

**Physical state** Liquid

**Odor** Slight Solvent

**Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling  
Do not eat, drink or smoke when using this product  
Use only outdoors or in a well-ventilated area  
Wear protective gloves/protective clothing/eye protection/face protection  
Do not breathe dust/fume/gas/mist/vapors/spray  
Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
Keep container tightly closed  
Ground/bond container and receiving equipment  
Use explosion-proof electrical/ventilating/lighting/./? /equipment  
Use only non-sparking tools  
Take precautionary measures against static discharge

**Precautionary Statements - Response**

IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
If eye irritation persists: Get medical advice/attention  
If skin irritation occurs: Get medical advice/attention  
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
Wash contaminated clothing before reuse  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
Call a POISON CENTER or doctor/physician if you feel unwell  
IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell  
Rinse mouth  
In case of fire: Use CO2, dry chemical, or foam for extinction

**Precautionary Statements - Storage**

Store locked up  
Store in a well-ventilated place. Keep cool

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

This product contains a material that can cause serious lung damage or impairment if inhaled as an aerosol or fine mist.

**Other Information**

DO NOT ATOMIZE DURING APPLICATION. DO NOT BUFF OR BURNISH AFTER APPLICATION  
4.89905% of the mixture consists of ingredient(s) of unknown toxicity

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS No	Weight-%	Trade Secret
Isobutyl triethoxysilane	18395-30-7	60 - 100	*

Isooctyl trimethoxy silane	34396-03-7	10 - 30	*
Mineral Spirits	64742-88-7	3 - 7	*
Methanol	67-56-1	1 - 5	*
Proprietary - Perfluoroalkyl acrylate copolymer	Undisclosed	1 - 5	*

\* The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

##### First aid measures

<b>General advice</b>	Immediate medical attention is required. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). If symptoms persist, call a physician.
<b>Eye contact</b>	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.
<b>Skin Contact</b>	Wash off immediately with plenty of water while removing contaminated clothing and shoes. If skin irritation persists, call a physician.
<b>Inhalation</b>	Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Call a physician.
<b>Ingestion</b>	Do NOT induce vomiting. Rinse mouth. Drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician.
<b>Self-protection of the first aider</b>	Remove all sources of ignition. Use personal protective equipment as required.

##### Most important symptoms and effects, both acute and delayed

<b>Symptoms</b>	Inhalation of mists or vapors may cause serious lung damage or impairment if inhaled. Causes eye and skin irritation. Harmful if swallowed.
-----------------	---

##### Indication of any immediate medical attention and special treatment needed

<b>Note to physicians</b>	Treat symptomatically.
---------------------------	------------------------

#### 5. FIRE-FIGHTING MEASURES

##### Suitable Extinguishing Media

Use. Dry chemical. Carbon dioxide (CO<sub>2</sub>). Water spray (fog). Alcohol resistant foam.

**Unsuitable Extinguishing Media** Do not use a solid water stream as it may scatter and spread fire.

##### Specific hazards arising from the chemical

Keep product and empty container away from heat and sources of ignition. Risk of ignition.

##### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

#### 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation, especially in confined areas. Keep people away from and upwind of spill/leak. Pay attention to flashback. Take precautionary measures against static discharges. Use personal protective equipment as required.

### Environmental precautions

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. See Section 12 for additional ecological information.

### Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so. Dike far ahead of liquid spill for later disposal.

**Methods for cleaning up** Dam up. Cover liquid spill with sand, earth or other non-combustible absorbent material. Pick up and transfer to properly labeled containers. Take precautionary measures against static discharges. Ground and bond containers when transferring material.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Advice on safe handling** Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray.

### Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat. Keep in properly labeled containers.

**Incompatible materials** Incompatible with oxidizing agents. Alkali. Aluminum. Ammonia. Halogens. Acids.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Methanol 67-56-1	STEL: 250 ppm TWA: 200 ppm S*	TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m <sup>3</sup> (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m <sup>3</sup> (vacated) S*	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> STEL: 250 ppm STEL: 325 mg/m <sup>3</sup>

NIOSH IDLH Immediately Dangerous to Life or Health

**Other Information** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

### Appropriate engineering controls

**Engineering Controls** Showers  
Eyewash stations  
Ventilation systems. DO NOT ATOMIZE DURING APPLICATION. DO NOT BUFF OR BURNISH AFTER APPLICATION.

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin and body protection** Wear protective gloves and protective clothing.

**Respiratory protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

**General Hygiene Considerations** Regular cleaning of equipment, work area and clothing is recommended. When using do not eat, drink or smoke.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical state</b>	Liquid	<b>Odor</b>	Slight Solvent
<b>Appearance</b>	clear	<b>Odor threshold</b>	No information available
<b>Color</b>	clear colorless		
<b>Property</b>	<b>Values</b>	<b>Remarks • Method</b>	
pH	Not Applicable	Not Applicable	
Melting point/freezing point	No information available		
Boiling point/boiling range	No information available		
Flash point	42 °C / 108 °F	ASTM D 3278	
Evaporation rate	No information available		
Flammability (solid, gas)	No information available		
Flammability Limits in Air			
Upper flammability limits	No information available		
Lower flammability limit	No information available		
Vapor pressure	No information available		
Vapor density	No information available		
Specific Gravity	.909		
Water solubility	Insoluble in water		
Solubility in other solvents	No information available		
Partition coefficient	No information available		
Autoignition temperature	No information available		
Decomposition temperature	No information available		
Kinematic viscosity	No information available		
Dynamic viscosity	No information available		
Explosive properties	Not an explosive		
Oxidizing properties	Not Applicable		

## 10. STABILITY AND REACTIVITY

### Reactivity

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of Hazardous Reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Incompatible with oxidizing agents. Alkali. Aluminum. Ammonia. Halogens. Acids.

**Hazardous Decomposition Products**

Carbon oxides. Formaldehyde. Carbonyl fluoride. Hydrogen fluoride.

**11. TOXICOLOGICAL INFORMATION**

**Information on likely routes of exposure**

<b>Product Information</b>	Irritating to eyes, skin and respiratory tract Harmful by inhalation and if swallowed Inhalation of mists or vapors may cause serious lung damage or impairment if inhaled
<b>Inhalation</b>	Avoid breathing vapors or mists. Harmful by inhalation. Inhalation of mists or vapors may cause serious lung damage or impairment if inhaled.
<b>Eye contact</b>	Severely irritating to eyes.
<b>Skin Contact</b>	Causes skin irritation.
<b>Ingestion</b>	Do not taste or swallow. Harmful if swallowed.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Mineral Spirits 64742-88-7	> 5000 mg/kg ( Rat )	= 3000 mg/kg ( Rabbit )	> 5.28 mg/L ( Rat ) 4 h
Methanol 67-56-1	= 5628 mg/kg ( Rat )	= 15800 mg/kg ( Rabbit )	= 83.2 mg/L ( Rat ) 4 h = 64000 ppm ( Rat ) 4 h

**Information on toxicological effects**

<b>Symptoms</b>	This product contains a material that can cause serious lung damage or impairment if inhaled as an aerosol or fine mist. May cause respiratory irritation. Causes serious eye irritation. Causes skin irritation. Harmful if swallowed.
-----------------	---

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

<b>Sensitization</b>	No information available.
<b>Germ cell mutagenicity</b>	No information available.
<b>Carcinogenicity</b>	No information available.
<b>Reproductive toxicity</b>	No information available.
<b>STOT - single exposure</b>	No information available.
<b>STOT - repeated exposure</b>	No information available.
<b>Target Organ Effects</b>	central nervous system, Eyes, Gastrointestinal tract (GI), Respiratory system, Skin.
<b>Aspiration hazard</b>	No information available.

**Numerical measures of toxicity - Product Information**

**Unknown Acute Toxicity** 4.89905% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 552 mg/kg  
ATEmix (dermal) 7192 mg/kg mg/l  
ATEmix (inhalation-dust/mist) 1.8 mg/l  
ATEmix (inhalation-vapor) 2330.6 mg/l

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Mineral Spirits 64742-88-7	450: 96 h Pseudokirchneriella subcapitata mg/L EC50	800: 96 h Pimephales promelas mg/L LC50 static	-	100: 48 h Daphnia magna mg/L EC50
Methanol 67-56-1	-	28200: 96 h Pimephales promelas mg/L LC50 flow-through 100: 96 h Pimephales promelas mg/L LC50 static 19500 - 20700: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 18 - 20: 96 h Oncorhynchus mykiss mL/L LC50 static 13500 - 17600: 96 h Lepomis macrochirus mg/L LC50 flow-through	-	-

### Persistence and degradability

No information available.

### Bioaccumulation

No information available.

Chemical Name	Partition coefficient
Methanol 67-56-1	-0.77

### Other adverse effects

No information available

## 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

**Disposal of wastes** Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Contaminated packaging** Do not reuse container.

**US EPA Waste Number** D001

This product contains one or more substances that are listed with the State of California as a hazardous waste.

## 14. TRANSPORT INFORMATION

**DOT** Not regulated (If shipped in NON BULK packaging by ground transport)  
**UN/ID No** UN1866  
**Proper shipping name** Resin Solution  
**Hazard Class** 3  
**Packing Group** III

**IATA**  
**UN/ID No** UN1866  
**Proper shipping name** Resin Solution  
**Hazard Class** 3  
**Packing Group** III

**IMDG**  
**UN/ID No** UN1866  
**Proper shipping name** Resin Solution  
**Hazard Class** 3  
**Packing Group** III

## 15. REGULATORY INFORMATION

### International Inventories

**TSCA** Complies  
**DSL/NDL** Complies

### Legend:

*TSCA - United States Toxic Substances Control Act Section 8(b) Inventory*  
*DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List*

### US Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Methanol - 67-56-1	67-56-1	1 - 5	1.0

#### **SARA 311/312 Hazard Categories**

**Acute health hazard** Yes  
**Chronic Health Hazard** No  
**Fire hazard** Yes  
**Sudden release of pressure hazard** No  
**Reactive Hazard** No

#### **CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)



**CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Methanol 67-56-1	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ

**US State Regulations****California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Methanol - 67-56-1	Developmental

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Mineral Spirits 64742-88-7	X	-	-
Methanol 67-56-1	X	X	X

**16. OTHER INFORMATION**

<b>NFPA</b>	Health hazards 3	Flammability 2	Instability 0	Physical and Chemical Properties -
<b>HMIS</b>	Health hazards 3	Flammability 2	Physical hazards 0	Personal protection X

Prepared By Regulatory Department  
Issue Date 07-Nov-2014  
Revision Date 07-Nov-2014  
Revision Note

No information available

**Disclaimer**

The information contained on the Material Safety Data Sheet has been compiled from data considered accurate. This data is believed to be reliable, but it must be pointed out that values for certain properties are known to vary from source to source. PROSOCO, Inc. expressly disclaims any warranty express or implied as well as any liability for any injury or loss arising from the use of this information or the materials described. This data is not to be construed as absolutely complete since additional data may be desirable when particular conditions or circumstances exist. It is the responsibility of the user to determine the best precautions necessary for the safe handling and use of this product for his unique application. This data relates only to the specific material designated and is not to be used in combination with any other material. Many federal and state regulations pertain directly or indirectly to the product's end use and disposal of containers and unused material. It is the purchaser's responsibility to familiarize himself with all applicable regulations.

End of Safety Data Sheet