

# MATERIAL SAFETY DATA SHEET

Sure Klean® Weather Seal Siloxane PD

## Section 1: PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** Sure Klean® Weather Seal Siloxane PD  
**Product Use:** Coating.  
**Manufacturer/Supplier:** Prosoco, Inc.  
3741 Greenway Circle  
Lawrence, KS  
66046  
**Phone Number:** 800-255-4255  
**Emergency Phone:** 800-535-5053  
**Date of Preparation:** January 9, 2012

## Section 2: HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

CAUTION

MAY CAUSE EYE IRRITATION. MAY CAUSE SKIN IRRITATION.

**Potential Health Effects:** See Section 11 for more information.

**Likely Routes of Exposure:** Skin contact and eye contact.

**Eye:** May cause eye irritation.

**Skin:** May cause skin irritation.

**Ingestion:** Not a normal route of exposure. May cause stomach distress, nausea or vomiting.

**Inhalation:** Not a normal route of exposure. Mist may cause respiratory tract irritation.

**Chronic Effects:** Prolonged or repeated contact may dry skin and cause irritation. Long term exposure may cause liver damage.

**Signs and Symptoms:** Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

**Medical Conditions Aggravated By Exposure:** Because of its irritating properties, product may aggravate pre-existing eye, and skin conditions.

**Target Organs:** Skin, eyes, liver.

**Potential Environmental Effects:** May cause long-term adverse effects in the aquatic environment. See Section 12 for more information.

## Section 3: COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	CAS #	Wt. %
Siloxanes and Silicones, di-Me, Me hydrogen	68037-59-2	3 - 7
Triethoxyoctylsilane	2943-75-1	3 - 7

## Section 4: FIRST AID MEASURES

**Eye Contact:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes, including under lids. If easy to do, remove contact lenses, if worn. Get medical attention.

# MATERIAL SAFETY DATA SHEET

Sure Klean® Weather Seal Siloxane PD

**Skin Contact:** In case of contact, immediately flush skin with plenty of soap and water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.

**Inhalation:** Not a normal route of exposure. If symptoms develop, remove to fresh air. Get medical attention if condition worsens.

**Ingestion:** If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Seek medical attention or call poison control.

**General Advice:** In case of accident or if you feel unwell, seek medical advice immediately (show the label or MSDS where possible).

**Note to Physicians:** Symptoms may not appear immediately.

## Section 5: FIRE FIGHTING MEASURES

**Flammability:** Not flammable by WHMIS criteria. Flammable vapours of ethyl alcohol and hydrogen gas may accumulate in the container under prolonged storage.

### Means of Extinction:

**Suitable Extinguishing Media:** Powder, water spray, foam, carbon dioxide.

**Unsuitable Extinguishing Media:** Not available.

**Products of Combustion:** May include, and are not limited to: oxides of carbon, oxides of nitrogen, silicon dioxide, hydrogen, formaldehyde.

### Explosion Data:

**Sensitivity to Mechanical Impact:** Not available.

**Sensitivity to Static Discharge:** Not available.

**Protection of Firefighters:** Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

## Section 6: ACCIDENTAL RELEASE MEASURES

**Personal Precautions:** Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental Precautions:** Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

**Methods for Containment:** Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

**Methods for Clean-Up:** Scoop up material and place in a disposal container. Provide ventilation. Spills of this material are a slipping hazard.

**Other Information:** Not available.

## Section 7: HANDLING AND STORAGE

### Handling:

Avoid contact with skin and eyes. Do not breathe gas/fumes/vapor/spray. Use only in well-ventilated areas. This product will continue to evolve vapour during drying and ethyl alcohol during curing. Continue ventilation as needed during curing (3-5 days). Handle and open container with care. When using do not eat or drink. Wash hands before eating, drinking, or smoking.

# MATERIAL SAFETY DATA SHEET

Sure Klean® Weather Seal Siloxane PD

## Storage:

Keep out of the reach of children. Keep container tightly closed and dry in a well-ventilated place. Store in a cool place, away from incompatibles.

## Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

### Exposure Guidelines

#### Ingredient

Siloxanes and Silicones, di-Me, Me hydrogen  
Triethoxyoctylsilane

#### Exposure Limits

##### ACGIH-TLV

Not available.

Not available.

**Engineering Controls:** Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

### Personal Protective Equipment:

**Eye/Face Protection:** Wear eye/face protection.

**Hand Protection:** Wear suitable gloves - nitrile, rubber, PVC.

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** In case of insufficient ventilation, wear suitable respiratory equipment.

**General Hygiene Considerations:** Handle according to established industrial hygiene and safety practices.

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b>	Not available.
<b>Colour:</b>	White.
<b>Odour:</b>	Odourless.
<b>Odour Threshold:</b>	Not available.
<b>Physical State:</b>	Liquid.
<b>pH:</b>	Not available.
<b>Viscosity:</b>	Not available.
<b>Freezing Point:</b>	Not available.
<b>Boiling Point:</b>	Not available.
<b>Flash Point:</b>	> 100 °C (212 °F)
<b>Evaporation Rate:</b>	Not available.
<b>Lower Flammability Limit:</b>	Not available.
<b>Upper Flammability Limit:</b>	Not available.
<b>Vapor Pressure:</b>	Not available.
<b>Vapor Density:</b>	Not available.
<b>Specific Gravity:</b>	0.996
<b>Solubility in Water:</b>	Complete.
<b>Coefficient of Water/Oil Distribution:</b>	Not available.
<b>Auto-ignition Temperature:</b>	Not available.

# MATERIAL SAFETY DATA SHEET

Sure Klean® Weather Seal Siloxane PD

**Percent Volatile, wt. %:** Not available.

**VOC content, wt. %:** Not available.

## Section 10: STABILITY AND REACTIVITY

**Stability:** Relatively non-reactive, but will hydrolyze slowly at ambient temperatures to form hydrogen and ethanol.

**Conditions of Reactivity:** Heat. Incompatible materials.

Incompatible Materials: Oxidizers. Moisture. Contact with water, alcohols, acids, bases, metals or metallic compounds may liberate flammable hydrogen gas. Do not repackage, dilute, or alter this product.

**Hazardous Decomposition Products:** May include, and are not limited to: oxides of carbon, oxides of nitrogen, silicon dioxide, hydrogen, formaldehyde. After long periods of time, small amounts of hydrogen gas and ethanol may be formed in the container headspace.

**Possibility of Hazardous Reactions:** No dangerous reaction known under conditions of normal use.

## Section 11: TOXICOLOGY INFORMATION

### EFFECTS OF ACUTE EXPOSURE

#### Component Analysis

Ingredient	LD <sub>50</sub> (oral)	LC <sub>50</sub>
Siloxanes and Silicones, di-Me, Me hydrogen	Not available.	Not available.
Triethoxyoctylsilane	10060 µL/kg, rat	Not available.
<b>Eye:</b>	May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.	
<b>Skin:</b>	May cause skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.	
<b>Ingestion:</b>	Not a normal route of exposure. May cause stomach distress, nausea or vomiting.	
<b>Inhalation:</b>	Not a normal route of exposure. Mist may cause respiratory tract irritation.	

### EFFECTS OF CHRONIC EXPOSURE

**Target Organs:** Not available.

**Chronic Effects:** Not hazardous by WHMIS criteria.

**Carcinogenicity:** Not hazardous by WHMIS criteria.

Ingredient	Chemical Listed as Carcinogen or Potential Carcinogen *
Siloxanes and Silicones, di-Me, Me hydrogen	Not listed.
Triethoxyoctylsilane	Not listed.

\* See Section 15 for more information.

**Mutagenicity:** Not hazardous by WHMIS criteria.

**Reproductive Effects:** Not hazardous by WHMIS criteria.

**Developmental Effects:**

**Teratogenicity:** Not hazardous by WHMIS criteria.

**Embryotoxicity:** Not hazardous by WHMIS criteria.

# MATERIAL SAFETY DATA SHEET

Sure Klean® Weather Seal Siloxane PD

**Respiratory Sensitization:** Not hazardous by WHMIS criteria.

**Skin Sensitization:** Not hazardous by WHMIS criteria.

**Toxicologically Synergistic Materials:** Not available.

## Section 12: ECOLOGICAL INFORMATION

**Ecotoxicity:** May cause long-term adverse effects in the aquatic environment.

**Persistence / Degradability:** Not available.

**Bioaccumulation / Accumulation:** Not available.

**Mobility in Environment:** Not available.

## Section 13: DISPOSAL CONSIDERATIONS

### Disposal Instructions:

This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

## Section 14: TRANSPORTATION INFORMATION

### TDG Classification

Not regulated

## Section 15: REGULATORY INFORMATION

### Federal Regulations

**Canadian:** This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

### Global Inventories

#### Ingredient

Siloxanes and Silicones, di-Me, Me hydrogen  
Triethoxyoctylsilane

#### Canada DSL/NDSL

DSL  
DSL

### HMIS - Hazardous Materials Identification System

Health - 1

Flammability - 0

Physical Hazard - 1

PPE – C

### NFPA - National Fire Protection Association:

Health - 1

Fire - 0

Reactivity - 1

**Hazard Rating:** 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

### WHMIS Classification(s):

Class D2B - Skin/Eye Irritant

### WHMIS Hazard Symbols:



# MATERIAL SAFETY DATA SHEET

Sure Klean® Weather Seal Siloxane PD

## SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

**OSHA (O)** Occupational Safety and Health Administration.

**ACGIH (G)** American Conference of Governmental Industrial Hygienists.

A1 - Confirmed human carcinogen.

A2 - Suspected human carcinogen.

A3 - Animal carcinogen.

A4 - Not classifiable as a human carcinogen.

A5 - Not suspected as a human carcinogen.

**IARC (I)** International Agency for Research on Cancer.

1 - The agent (mixture) is carcinogenic to humans.

2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.

2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.

3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.

4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.

**NTP (N)** National Toxicology Program.

1 - Known to be carcinogens.

2 - Reasonably anticipated to be carcinogens.

## Section 16: OTHER INFORMATION

### Disclaimer:

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

**Expiry Date:** January 9, 2015

**Version #:** 1.0

**Prepared by:** Nexreg Compliance Inc.

Phone: (519) 488-5126

[www.nexreg.com](http://www.nexreg.com)