

Capri (CP)

Upholstery Leather

Technical Data

Leather Specifications

Style	Capri (CP)
Description	Full grain, aniline dyed
Thickness	1.2–1.4 mm
Weight	3.0–3.5 oz. per sq. ft.
Average Hide Size	55–60 sq. ft.
Finish:	Breathable, light, protective finish

Performance Characteristics**Tests**

Light Fastness (AATCC Method 16, Option E, 72 Hours)	Class 4
Crocking (ASTM D5053)	Dry: Class 4 Wet: Class 3
Abrasion (ASTM D7255)	300+ cycles (CS-10 wheels)
Flex (ASTM D2097)	70,000 flexes
Tearing Strength, Double Hole (ASTM D4705)	25 lbs.
Breaking Force (ASTM D2208)	200 lbs.
Elongation (ASTM D2211)	30-50% at 50 lbs.

Flammability*Passes the following flammability tests*

California Technical Bulletin 117	Complies
Boston Fire Dept. BFD IX-1	Complies (with flame treatment)
Surface Burning Characteristics of Bldg. Materials (ASTM E84)	Class I with flame treatment

*Successfully used in CAL 133 applications with Firegard F187 fire backer material or equivalent.

Recommended Cleaning Instructions

Dust regularly. Minor spots can be washed off using lukewarm water and mild soap.

Do not soak. Never clean with abrasive solvents, alcohol, or wax-based products.

Approved maintenance products are available from Spinneybeck.