

## Cervo (CV)

## Upholstery Leather

## Technical Data

**Leather Specifications**

Style	Cervo (CV)
Description	Full grain, aniline dyed leather GREENGUARD Certified
Thickness	1.4–1.6 mm
Weight	3.5–4.0 oz. per sq. ft.
Average Hide Size	50–55 sq. ft.
Finish	Naked

**Performance Characteristics****Tests**

Light Fastness (AATCC Method 16, Option E, 72 Hours)	Class 3
Crocking (ASTM D5053)	Dry: Class 4
Abrasion (ASTM D7255)	N/A
Flex (ASTM D2097)	N/A
Tearing Strength, Double Hole (ASTM D4705)	50 lbs.
Breaking Force (ASTM D2208)	500 lbs.
Elongation (ASTM D2211)	30–50% at 50 lbs.

**Flammability**

Passes the following flammability tests

California Technical Bulletin 117	Complies
Surface Burning Characteristics of Bldg. Materials (ASTM E84)	Class I with flame treatment

\*Successfully used in CAL 133 applications with Firegard F187 fire backer material or equivalent.

**Recommended Cleaning Instructions**

Dust regularly. Minor spots can be washed off using lukewarm water and mild soap.

Do not soak. Never clean with abrasive solvents, alcohol, or wax-based products.

Approved maintenance products are available from Spinneybeck.