Spinneybeck Technical Data Sheet

Acqua (AU) (Page 1 of 2)

Upholstery Leather	Technical Data
Leather Specifications	
Style	Acqua (AU)
Description	Corrected grain, aniline dyed,
	heavily finished leather
	GREENGUARD Certified
Thickness	1.0–1.1 mm
Weight	2.50-2.75 oz. per sq. ft.
Average Hide Size	55–65 sq. ft.
Finish	Breathable protective water-resistant finish
Performance Characteristics	Tests
Light Fastness (AATCC Method 16, Option E, 72 Hours)	Class 5
Crocking (ASTM D5053)	Dry: Class 4 Wet: Class 4
Abrasion (ASTM D7255)	300+ cycles (H-18 wheels)
	3,000+ cycles (CS-10 wheels)
Flex (ASTM D2097)	70,000 flexes
Tearing Strength, Double Hole (ASTM D4705)	40 lbs.
Breaking Force (ASTM D2208)	250 lbs.
Elongation (ASTM D2211)	30-50% at 50 lbs.
Flammability	Passes the following flammability tests
California Technical Bulletin 117	Complies
Boston Fire Dept. BFD IX-1	Complies (with flame treatment)
Cigarette Ignition Resistance (NFPA-260)	Class I
Surface Burning Characteristics of Bldg. Materials (ASTM E84)	Class I with flame treatment
IMO Resolution A.652 (16)	Complies

*Successfully used in CAL 133 applications with Firegard F187 fire backer material or equivalent.

Spinneybeck

Technical Data Sheet

Acqua (AU) (Page 2 of 2)

Upholstery Leather	Technical Data (continued)
Healthcare	
AATCC Test Method 22	
Water Repellency: Spray Test	Rating: 80
AATCC Test Method 100	
antibacterial Finishes on Textile Materials (Quantitative Test)	
Staphylococcus aureus	99.93% Reduction of Bacteria
Klebsiella pneumoniae	99.94% Reduction of Bacteria
AATCC Test Method 127	
Water Resistance	
Hydrostatic Pressure Test	129.0 cm avg.
AATCC Test Method 130	
Stain Release; Spot Clean Method	
Blood, Urine, Bleach	Immediate Grade 5.0; 24 Hr Grade 5.0
Betadine (bleach cleaning)	Immediate Grade 4.5-5.0; 24 Hr Grade 4.5
Nail Polish Remover	Immediate Grade 4.0-5.0
UFAC Test Method 1990	
UFAC Test Method 1990 Cigarette Ignition Resistance of Fabric	

Recommended Cleaning Instructions

Dust regularly. Minor spots can be washed off using lukewarm water and mild soap.

Do not soak. Never clean with abrasive solvents, alcohol, or wax-based products.

Approved maintenance products are available from Spinneybeck.