

**Upholstery Leather**

## Technical Data

**Leather Specifications**

Style	Maremma (MM)
Description	Full grain, aniline dyed, textured suede GREENGUARD Certified
Thickness	1.2–1.3 mm
Weight	3.0–3.25 oz. per sq. ft.
Average Hide Size	18–22 sq. ft.
Finish	Sueded with inherent soil-resistant treatment

**Performance Characteristics**

## Tests

Light Fastness (AATCC Method 16, Option E, 72 Hours)	Class 2-3
Crocking (ASTM D5053)	Dry: Class 2-3
Abrasion (ASTM D7255)	N/A
Flex (ASTM D2097)	N/A
Tearing Strength, Double Hole (ASTM D4705)	25 lbs.
Breaking Force (ASTM D2208)	175 lbs.
Elongation (ASTM D2211)	30–50% at 50 lbs.

**Flammability**

Passes the following flammability tests

California Technical Bulletin 117	Complies
-----------------------------------	----------

\*Successfully used in CAL 133 applications with Firegard F187 fire backer material or equivalent.

**Recommended Cleaning Instructions**

Dust regularly. Minor spots can be washed off using lukewarm water and mild soap.

Do not soak. Never clean with abrasive solvents, alcohol, or wax-based products.