

performance broadloom specifications

style name	thrive ecoworx® performance bl
style number	60762
construction	multi-level pattern loop
fiber	eco solution q® nylon
dye method	100% solution dyed

	english	metric

pattern repeat	14.4" w x 24" l	36.58 cm w x 60.96 cm l
tufted weight	26.0	881.55 g/m ²
gauge	1/10	39.37 per 10 cm
stitches per inch	13.0	51.18 per 10 cm
finished pile thickness	0.138	3.51 mm
total thickness	0.244	6.20 mm
average density	6783	12.63 kilotex
product size	12 foot	3.66 m
primary backing	synthetic	
secondary backing	ecoworx® performance broadloom	
protective treatments	ssp® shaw soil protection	

testing

radiant panel	Class I
nbs smoke	less than 450
electrostatic propensity	less than 3.5 kv

warranties

lifetime commercial limited

installation method

direct glue

coordinating products

prosper ecoworx® performance bl, accomplish ecoworx® performance bl, accomplish classicbac®, prosper classicbac®, aspire ecoworx® performance bl, aspire classicbac®, thrive classicbac®

environmental certification

nsf140 platinum
cradle to cradle silver certified



Specifications are subject to nominal manufacturing variances.

Material supply and/or manufacturing processes may necessitate changes without notice.

shawcontractgroup.com | 1 800.257.7429

eco impacts

thrive ecoworx® performance bl

end of life

recyclability100% recyclable

environmental guaranteefree pick up & recycling

To recycle call 800.509.SHAW

materials

ingredients

face fiber
dye method
backing
surface treatments
does not contain PVC, phthalates, or PBD/PBDE

nylon 6
100% solution dyed
polyolefin composite
non c8 fluorocarbon chemistry

recycled content

total recycled content (by weight)
pre-consumer
post-consumer
bio-based/rapidly renewable content (by weight)
packaging
country of origin (manufacturer)

30.3 %
7.9 %
22.4 %
0.0 %
100% recyclable
USA

Meets or exceeds all local and national regulations in country of manufacture.
Manufactured in an ISO9001 & ISO14001 certified facility or equivalent.
Recycled content is calculated using system allocation, mass balance, and direct insertion.
The actual recycled content in this product will likely vary. For more information email info@shawgreenedge.com.

third party certifications

MBDC cradle to cradle
NSF 140
CRI green label plus
USGBC LEED
Good Environmental Choice Australia
Singapore green label

silver certified
platinum certified
certified glp9968
contributes
certified
certified 039-003