

## performance broadloom specifications

style name	digits
style number	60767
construction	multi-level pattern loop
fiber	solution q extreme® nylon
dye method	100% solution dyed

	english	metric
-----		
pattern repeat	72"w x 96"l	182.88 cm w x 243.84 cm l
tufted weight	22.0	745.93 g/m <sup>2</sup>
gauge	1/12	47.24 per 10 cm
stitches per inch	11.5	45.28 per 10 cm
finished pile thickness	0.111	2.82 mm
total thickness		
average density	7135	13.29 kilotex
product size	12 foot	3.66 m
primary backing	synthetic	
secondary backing	ecoworx® performance broadloom	
protective treatments	inherent stain resistance	

## testing

radiant panel	Class I
nbs smoke	less than 450
electrostatic propensity	less than 3.5 kv

## warranties

lifetime commercial limited

## installation method

direct glue

## coordinating products

copy tile, construct tile, rotate tile, collage

## environmental certification

nsf140 platinum  
cradle to cradle silver certified



Specifications are subject to nominal manufacturing variances.  
Material supply and/or manufacturing processes may necessitate changes without notice.

shawcontractgroup.com | 1 800.257.7429

eco impacts

end of life

recyclability	100% recyclable
environmental guarantee	free pick up & recycling
To recycle call 800.509.SHAW	

materials

ingredients

face fiber	nylon 6
dye method	100% solution dyed
backing	polyolefin composite
does not contain PVC, phthalates, or PBD/PBDE	

recycled content

total recycled content (by weight)	10.7 %
pre-consumer	0.0 %
post-consumer	10.7 %
bio-based/rapidly renewable content (by weight)	0.0 %
packaging	100% recyclable
country of origin (manufacturer)	USA

Meets or exceeds all local and national regulations in country of manufacture.  
Manufactured in an ISO9001 & ISO14001 certified facility or equivalent.  
Recycled content is calculated using system allocation, mass balance, and direct insertion.  
The actual recycled content in this product will likely vary. For more information email [info@shawgreenedge.com](mailto:info@shawgreenedge.com).

third party certifications

MBDC cradle to cradle	silver certified
NSF 140	platinum certified
CRI green label plus	certified glp9968
USGBC LEED	contributes
Good Environmental Choice Australia	certified

Sustainability Through Innovation™ That's the Shaw Green Edge®