



Installation Methods



Quarter-Turn

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see <http://www.interface.com/disclaimer>

Product Post **Color** 2629 Print **Collection** Herald, Post & Times **Backing** GlasBac[®] RE Tile

Product Specifications

Product Number	123400250H
Product Construction	Tufted Cut & Loop
Yarn Manufacturer	Universal
Yarn System	Post-Consumer Content Type 6,6 Nylon
Dye Method	100% Solution Dyed
Soil/Stain Protection	Protekt ² [®]
Preservative Protection	Intersept [®]

	Imperial	Metric
Tufted Yarn Weight	24 oz/yd ²	
Machine Gauge	5/64 in	
Pile Height	0.22 in	
Pile Thickness	0.146 in	
Stitches	11 /in	
Pile Density	5918 oz/yd ²	
Size Imperial	19.69 in x 19.69 in	

Performance Specifications

Flooring Radiant Panel	(ASTM E-648) Class 1
Smoke Density	(ASTM E - 662)
Lightfastness	(AATCC 16 - E)
Static	(AATCC - 134) < 3.0 KV
Dimensional Stability	AACHEN Din 54318 <.10%
Preservative Efficacy	(AATCC 138 Washed) (AATCC 174 Parts 2&3) Intersept [®]

Environmental Specifications

Total Recycled Content	67%
Recycled Content (Post Industrial)	35%
Recycled Content (Post Consumer)	32%
Ingredients and Life Cycle Impacts	Environmental Product Declaration
End of Life	Carpet to Carpet Recycling

Technical Information

Maintenance	See recommended Interface Maintenance Guidelines online
Reclamation	Recyclable through ReEntry [®] 2.0 - Call 1.888.733.6873 (U.S.) / 1.866.398.3191 (Canada)
Manufacturing Location	ISO 9001 & 14001 Certified facilities in Troup County, Georgia, United States

View This Online

To view more information about Post, visit the following webpage in your browser:
<http://interfacehospitality.com/product/1490001999R45S001>