

ARTISTIC TILE

CREMA MARFIL SLAB

Quarried in Spain, CREMA MARFIL is a true classic. Subtle veining highlights a soothing neutral creamy-beige background, making polished CREMA MARFIL the perfect choice for both contemporary and traditional aesthetics. These slabs complement our CREMA MARFIL field tiles and mosaics beautifully!



polished



LIMESTONE/
MARBLE

APPLICATIONS

| Acid Sensitivity* | Counter Top | Interior Floor | Interior Wall | Shower Wall* | Shower Floor* | Exterior Floor | Exterior Wall | Pool / Fountain |
|-------------------|-------------|---------------------------|------------------------|--------------|---------------|----------------|---------------|-----------------|
| High | Yes | Medium Traffic Commercial | All, excluding showers | No | No | No | No | No |

INSTALLATION / MAINTENANCE

| Setting Material* | Grout | Grout Joint* | Membrane | Caulk | Sealer | Cleaner | Installation Instruction | Dry Layout |
|--------------------|------------------------------|-----------------|-------------------------------|------------------------|------------------------------|------------------------------------|--------------------------|------------|
| Mapei Kerapoxy 410 | Mapei Ultracolor Plus Sanded | See Notes Below | Mapei Mapelastick AquaDefense | Mapei Keracaulk Sanded | AquaMix Sealer's Choice Gold | AquaMix Conc. Stone & Tile Cleaner | MIA DSDM | Required |

NOTES

*Acid Sensitivity: This material is highly sensitive to acids. When used as a kitchen countertop, acid etching will be highly visible. Do not use this material if acid etching is a concern. For kitchen countertops we recommend a honed finish. Expect material to patina over time and create a beautiful rustic/antique look.

*Shower Wall & Floor: Per MIA guidelines, fiberglass mesh backed slabs are not recommended for showers.

*Setting Material: Horizontal applications. Vertical applications of 3cm material require anchoring.

May have fiberglass mesh backing, choose setting materials accordingly.


*Grout Joint: Interior flooring - 1/8" minimum, interior walls - 1/4" minimum, exterior paving - 1/4" minimum, exterior walls - 3/8".

*Tailored To Customization: Finish - on smaller cut-to-size pieces, 28" maximum width.

Tech Note: Alternate finishes and thicker formats available on special order as required for heavy commercial, exterior and other special applications.

VARIATION

TAILORED TO CUSTOMIZATION*



| Carpet Cutting |
|----------------|
| Field |
| Finish |
| Mosaic |
| Saddle |
| Vanity Top |
| Waterjet |



Slab
3/4 (2cm)
polished