

# W21361 Wingate by Wyndham

## Winter - Fall Scheme #CP-4 Guestrooms

### CARPET SPECIFICATIONS

#### CONSTRUCTION

#### PILE FIBER

#### STITCH RATE

#### PILE HEIGHT

#### TUFTED PILE WEIGHT

#### PRIMARY BACKING

#### SECONDARY BACKING

#### WIDTH

#### DENSITY FACTOR

#### WEIGHT DENSITY FACTOR

#### WARRANTY

#### SOIL & STAIN TREATMENT

#### PATTERN REPEAT

#### CERTIFICATION

#### TESTING DATA

**1/8 TIP-SHEARED LOOP SCROLL**

**100% SOLUTION DYED NYLON**

**15 SPI**

**.198**

**32 oz**

**WOVEN POLYPROPYLENE**

**ACTIONBAC**

**12'0"**

**5,818**

**186,182**

**TEN YEAR LIMITED WEAR**

**SCOTCHGARD**

**W 15" X L 10"**

**CARPET & RUG INSTITUTE GLP5076**

**ASTM E-648 Flooring Radiant Panel: Class I**

**DOC-FF1-70 Methenamine Pill Test: Passes**

**AATCC 134 Electrostatic Propensity: Less than 3.5 KV**

**E0622 Smoke Chamber: Less than 450**



Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Material supply and /or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

This carpet is manufactured and recommended for floor covering use only. As in all quality carpet, colors are subject to dye lot variations. For optimum side match and finished seam appearance, this product should be installed whenever possible, with seams running perpendicular to major external (outside) light sources.

The equipment used to manufacture patterned (graphics) carpet may create visible lines in both length and width directions. This characteristic will not always be detectable in small samples and is not considered a manufacturing defect.

As with all patterned carpets, perfect pattern match may not be obtainable at seams. Tolerances in pattern registration – bow and skew – are to be expected. Reasonable pattern matches may be obtained by using trained, experienced professional installers and by following the manufacturers' installation procedures. Chair pads are recommended under office chairs with rollers to preserve appearance retention, avoid premature or accelerated wear, and act as a deterrent toward delamination. Special backing systems are available that do not require chair pads.

Walk off mats are recommended at building entry ways to reduce soiling. Recommended adhesive is 2800 Multi Purpose Latex Adhesive and 1801 Universal Seam Sealer.

For samples, specifications, or other information please contact your sales representative.

**Signature**  
Hospitality Carpets



2222 S Hamilton Street  
Dalton, Georgia 30721  
[www.signaturehospitalitycarpets.com](http://www.signaturehospitalitycarpets.com)  
TF: 800.809.7086 - F: 706.270.8779