

Interior/Exterior Acrylic Block Filler

Architectural Coating - Premium

Description

A premium acrylic interior and exterior heavy-bodied block filler designed to fill voids in concrete, block, masonry and brick without shrinking or cracking. Compatible with alkyd and acrylic topcoats.

Recommended Uses

New or previously painted concrete, block, masonry and brick.

Colors

White

Packaging

Five gallon containers

Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. Glossy or slick surfaces must be scuff sanded prior to application of paint coatings.

Primer

Masonry / Concrete / Block 4600 Uniprime II

Application

Brush, roll or spray. If sprayed, follow immediately with a paint roller to work the material into the surface. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Clean tools and equipment with soap and water.

Drying Time

Touch: 2 hours
Recoat: 8 hours

Coverage

75 – 250 square feet per gallon, depending on surface.

Mil Thickness

Wet = 18.0 - 22.4 Dry = 8.4 - 10.4

Thinning

Use at package consistency. If thinning is required, use water sparingly.

Composition

Titanium Dioxide	7.1%
Extenders	41.6%
TOTAL PIGMENT	48.7%

Vinyl Acrylic Resin	12.6%
Additives	7.2%
Water	31.5%
TOTAL VEHICLE	51.3%

Weights & Measurements +/-3.0%

Solids by Volume:	50.3%
Solids by Weight:	66.3%
VOC:	23 g/l
Weight Per Gal:	12.3 lbs.
Viscosity:	94 - 98 KU

Conformance

SCAQMD - complies with Rule 1113, Architectural Coatings

LEED - complies with LEED 2009
-Low Emitting Materials

MPI - #4

DISCLAIMER: To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.

Revised 03.15