

Seal Kote 155

Interior PVA Sealer

Architectural Coating - Premium

#### Description

A premium waterbased pigmented PVA sealer for interior use on drywall. Seals the substrate providing a good foundation for acrylic topcoats.

### Recommended Uses

New interior drywall and plaster.

# <u>Colors</u>

White

### **Packaging**

One and five gallon containers

# Surface Preparation

Surfaces must be clean, dry and free from all contaminants & residual dust that may impair adhesion. Not recommended for use over previously painted surfaces.

#### <u>Application</u>

Brush, roll or spray. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Clean tools and equipment with soap and water.

#### Drying Time

Touch: 30 minutes
Recoat: 2 hours

#### <u>Coverage</u>

250 – 375 square feet per gallon, depending on surface.

# Mil Thickness

Vet = 4.2 Dry = 1.3

### **Thinning**

Use at package consistency. If thinning is required, use water sparingly.

#### **Composition**

TOTAL PIGMENT	23.2%
Extenders	13.6%
Titanium Dioxide	9.6%

 Resin
 17.7%

 Additives
 4.0%

 Water
 55.1%

 TOTAL VEHICLE
 76.8%

Weights & Measurements +/-3.0%

Solids by Volume: 31.0%
Solids by Weight: 41.9%
VOC: 47 g/l
Weight Per Gal: 10.1 lbs.
Viscosity: 90 - 94 KU

#### Conformance

SCAQMD - complies with Rule 1113, Architectural Coatings

LEED - complies with LEED 2009
-Low Emitting Materials

DISCLAIMER: To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranties does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.

Revised 09.15