

Exterior 100% Acrylic Velvet Flat Finish

Architectural Coating - Premium Plus

Description

A premium plus 100% acrylic velvet flat finish for exterior use. Provides a tough flexible film with outstanding resistance to fading and chalking. Exhibits excellent color retention, hide and adhesion. Superior stain resistance and washability with outstanding mildew resistance.

Recommended Uses

New or previously painted wood, stucco, concrete, masonry and properly primed metal.

Colors

White, stock colors and custom colors to order.
Bases: White, A, D, H and P

Packaging

Quart, one and five gallon containers

Finish

Flat, sheen @ 85° = 4.1 - 4.7%

Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. Glossy or slick surfaces must be scuff sanded prior to application of paint coatings and may require priming. Woods prone to extractive bleeding, such as cedar and redwood require a stain blocking primer.

Primer

Drywall (New):	155 Seal Kote
	1100 Hi-Build PVA Sealer
Drywall (Existing):	4000 Uniprime
Concrete/Masonry:	4600 Uniprime II
Wood (Exterior):	4200 Terminator II
Ferrous Metal:	9600 Protec Metal Prime White
	9610 Protec Metal Prime
	Red Oxide
Non-Ferrous Metal:	4800 Metal Pro Primer White
	4810 Metal Pro Primer
	Red Oxide

Application

Brush, roll or spray. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Clean tools and equipment with soap and water.

Drying Time

Touch:	1 hour
Recoat:	4 - 6 hours

Coverage

350 - 420 square feet per gallon, depending on surface.

Mil Thickness

Wet = 3.7	Dry = 1.6
-----------	-----------

Thinning

Use at package consistency. If thinning is required, use water sparingly.

Composition

Titanium Dioxide	13.8%
Extenders	22.0%
TOTAL PIGMENT	35.8%

Acrylic Resin	20.0%
Additives	2.1%
Water	42.1%
TOTAL VEHICLE	64.2%

Weights & Measurements +/-3.0%

Solids by Volume:	43.0%
Solids by Weight:	56.2%
VOC:	45 g/l
Weight Per Gal:	11.0 lbs.
Viscosity:	94 - 98 KU

Conformance

SCAQMD - complies with Rule 1113, Architectural Coatings
MPI - #16

DISCLAIMER: To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.

Revised 03.15