



# V-PRO 300 Semi-Gloss

## 340

Zero\* V.O.C. Interior Latex Semi-Gloss

Architectural Coating - Quality

340 V-PRO 300 Semi-Gloss Zero\* V.O.C. Interior Latex Semi-Gloss

### Description

V-PRO 300 (340 Semi-Gloss) is a zero\* VOC interior professional grade latex semi-gloss for use on properly primed walls and ceilings including masonry, plaster, concrete, acoustic, wood and metal surfaces. This products offers good washability, scrubability and gloss uniformity.

### Recommended Uses

Designed for the repaint maintenance and housing residential markets where a semi-gloss is desired. NOT recommended for horizontal surfaces such as shelves and paneling.

### Colors

Tintable White

### Packaging

Five gallon containers

### Finish

Semi-Gloss, sheen @ 60° = 35.0 – 45.0%

### Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. Glossy or slick surfaces must be scuff sanded prior to application of paint coatings and may require priming.

### Primer

Masonry/Concrete:	V-PRO 301 Primer
Drywall (New):	V-PRO 301 Primer
Drywall (Existing):	4000 Uniprime
	8000 Carefree Prime-ZALL
Wood:	4000 Uniprime
	8000 Carefree Prime-ZALL
Metal:	9600 Protec Metal Prime
Glossy Surfaces:	4000 Uniprime

### Application

Brush, roll or spray. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Light overspray can be cleaned up with water even after drying. Clean tools and equipment with soap and water.

### Drying Time

Touch:	2 hours
Recoat:	4 hours

### Coverage

350 – 400 square feet per gallon, depending on surface.

### Mil Thickness

Wet = 4.0	Dry = 1.3
-----------	-----------

### Thinning

Use at package consistency. If thinning is required, use water sparingly.

### Composition

Titanium Dioxide	17.9%
Extenders	6.1%
<b>TOTAL PIGMENT</b>	<b>24.0%</b>

Latex Resin	19.4%
Additives	6.4%
Water	50.2%
<b>TOTAL VEHICLE</b>	<b>76.0%</b>

Weights & Measurements +/-3.0%

Solids by Volume:	30.4%
Solids by Weight:	41.4%
VOC:	<2 g/l
Weight Per Gal:	9.9 lbs.
Viscosity:	96-102 KU

### Conformance

**SCAQMD** - complies with Rule 1113, Architectural Coatings

**LEED** - complies with LEED 2009  
-Low Emitting Materials

\*NOTE: Zero VOC is defined as no VOC containing solvents added in the manufacturing process of this product. Slight traces of VOC are present in additives used in manufacturing. This product has less than half the allowable VOC of the SCAQMD Super Compliant Coatings category.

**DISCLAIMER:** To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.

Revised 01.16