



## Interior/Exterior 100% Acrylic Primer

Architectural Coating - Premium Plus

### Description

A premium plus, multi-purpose 100% acrylic primer for exterior and interior applications. Superior resistance to efflorescence and alkalinity on concrete and masonry. Dries to a durable film which provides an excellent base for all top coats.

### Recommended Uses

New concrete, masonry, wood, galvanized metal and aluminum. This product can also be used on most previously painted surfaces.

### Colors

White (tint with up to 2 oz. of colorant). Also available in 4010 Red Oxide and 40D deep tint base (tint with up to 8 oz. of colorant).

### Packaging

Quarts, one and five gallon containers

### Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. Glossy or slick surfaces must be scuff sanded prior to application of paint coatings and may require priming. Woods prone to extractive bleeding require a stain blocking primer.

### Application

Brush, roll or spray. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Clean tools and equipment with soap and water.

### Drying Time

Touch: 30 minutes  
Recoat: 2 - 4 hours

### Coverage

350 - 450 square feet per gallon, depending on surface.

### Mil Thickness

Wet = 4.0      Dry = 1.8

### Thinning

Use at package consistency. If thinning is required, use water sparingly.

### Composition

Titanium Dioxide	11.8%
Extenders	17.4%
<b>TOTAL PIGMENT</b>	<b>29.2%</b>

Proprietary Resin	22.1%
Additives	4.1%
Water	44.6%
<b>TOTAL VEHICLE</b>	<b>70.8%</b>

Weights & Measurements +/-3.0%

Solids by Volume:	39.0%
Solids by Weight:	53.6%
VOC:	48 g/l
Weight Per Gal:	10.9 lbs.
Viscosity:	92 - 96 KU

### Conformance

**SCAQMD** - complies with Rule 1113, Architectural Coatings

**LEED** - complies with LEED 2009

-Low Emitting Materials

**MPI** - #6

**DISCLAIMER:** To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.

Revised 01.16