

### Interior / Exterior 100% Acrylic Epoxy Primer

Architectural Coating - Premium Plus

#### Description

A premium plus 100% acrylic epoxy fortified masonry primer. Specially formulated for use on new and existing concrete and masonry surfaces. Superior resistance to efflorescence and alkalinity. Provides outstanding adhesion. Excellent primer for masonry top coats.

#### Recommended Uses

Masonry, concrete, stucco and brick. Excellent choice for new tilt-up construction.

#### Colors

White  
Bases: P (factory tint)

#### Packaging

Five gallon containers

#### Surface Preparation

New masonry surfaces should be properly cured and have a pH balance not greater than 12. Clean all dirt, sacking material, grease, bond breakers and all other contaminants that may impair adhesion. Glossy or slick surfaces must be scuff sanded.

#### Application

Brush, roll or spray. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Clean tools and equipment with soap and water.

#### Drying Time

Touch: 1 hour  
Recoat: 4 hours

#### Coverage

200 – 300 square feet per gallon, depending on surface.

#### Mil Thickness

Wet = 4.8      Dry = 2.0

#### Thinning

Use at package consistency. If thinning is required, use water sparingly.

#### Composition

Titanium Dioxide	12.6%
Extenders	26.0%
<b>TOTAL PIGMENT</b>	<b>38.6%</b>

Acrylic Resin	16.2%
Additives	7.2%
Water	38.0%
<b>TOTAL VEHICLE</b>	<b>61.4%</b>

Weights & Measurements +/-3.0%

Solids by Volume:	41.4%
Solids by Weight:	57.9%
VOC:	47 g/l
Weight Per Gal:	11.5 lbs.
Viscosity:	96 - 98 KU

#### Conformance

**SCAQMD** - complies with Rule 1113, Architectural Coatings

**LEED** - complies with LEED 2009 and LEEDv4  
-Low Emitting Materials

**CDPH Section 01350** - tested and passed

**MPI** - #3

**DISCLAIMER:** To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.

Revised 01.16