

## Interior /Exterior Epoxy-Ester Acrylic Primer

Architectural Coating - Premium

### Description

A premium epoxy-ester modified acrylic primer. Designed for use over concrete tilt-up, masonry and plaster surfaces. Promotes adhesion and resists alkali and efflorescence. May be used on surfaces that have tested 12 or lower on the pH scale.

### Recommended Uses

Interior/exterior primer on new tilt up, concrete, stucco and other masonry substrates.

### Colors

White

### Packaging

Five gallon containers

### Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion prior to application of paint coatings.

### Application

Brush, roll or spray. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Clean tools and equipment with soap and water.

### Drying Time

Touch: 1 hour  
Recoat: 4 hours

### Coverage

375 – 425 square feet per gallon, depending on surface.

### Mil Thickness

Wet = 3.7 Dry = 1.5

### Thinning

Use at package consistency. If thinning is required, use water sparingly.

### Composition

Titanium Dioxide	10.1%
Extenders	27.2%
<b>TOTAL PIGMENT</b>	<b>37.3%</b>

Acrylic Resin	16.9%
Additives/Solvents	5.0%
Water	40.8%
<b>TOTAL VEHICLE</b>	<b>62.7%</b>

Weights & Measurements +/-3.0%

Solids by Volume:	40.1%
Solids by Weight:	56.1%
VOC:	41 g/l
Weight Per Gal:	11.3 lbs.
Viscosity:	92 - 96 KU

### Conformance

**SCAQMD** - complies with Rule 1113, Architectural Coatings

**LEED** - complies with LEED 2009

-Low Emitting Materials

**DISCLAIMER:** To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.

Revised 03.15