



V-PRO 5000 Eggshell

5300

Zero* V.O.C., Low Odor Interior/Exterior Latex Eggshell

Architectural Coating - Quality Plus

5300 V-PRO 5000 Eggshell Zero* V.O.C., Low Odor Interior/Exterior Latex Eggshell

Description

V-PRO 5000 (5300 Eggshell) is a zero* VOC, interior/exterior quality latex eggshell for use on primed walls and ceilings including masonry, plaster, concrete, acoustic, wood and metal surfaces. This product offers excellent washability, high scrubability, gloss uniformity and minimizes wall imperfections. **NOTE:** This product contains ingredients which resist the growth of microbes on the surface of the paint film.

Recommended Uses

Designed for commercial and institutional projects where a durable low sheen is required on new interior drywall, plaster, masonry, concrete, block, tilt-ups and acoustic surfaces. NOT recommended for horizontal surfaces such as shelves and paneling.

Colors

Tintable White

Bases: A and D

Packaging

One and five gallon containers

Finish

Eggshell, sheen @ 60° = 14.0 – 17.0%

Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. Glossy or slick surfaces must be scuff sanded prior to application of paint coatings and may require priming.

Primer

Masonry/Concrete (Int.): V-PRO 5001 Primer

(Ext.): 4000 Uniprime

Drywall (New): V-PRO 5001 Primer

Drywall (Existing): 4000 Uniprime

8000 Carefree Prime-ZALL

Wood: 4000 Uniprime

8000 Carefree Prime-ZALL

Metal: 9600 Protec Metal Prime

Glossy Surfaces: 4000 Uniprime

Application

Brush, roll or spray. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Light overspray can be cleaned up with water even after drying. Clean tools and equipment with soap and water.

DISCLAIMER: To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.

Revised 01.16

Drying Time

Touch: 1 hour

Recoat: 4 hours

Coverage

350 – 400 square feet per gallon, depending on surface.

Mil Thickness

Wet = 4.5 Dry = 1.8

Thinning

Use at package consistency. If thinning is required, use water sparingly.

Composition

Titanium Dioxide 13.4%

Extenders 18.0%

TOTAL PIGMENT 31.4%

Latex Resin 19.2%

Additives 4.3%

Water 45.1%

TOTAL VEHICLE 68.6%

Weights & Measurements +/-3.0%

Solids by Volume: 42.0%

Solids by Weight: 56.1%

VOC: <2 g/l

Weight Per Gal: 11.0 lbs.

Viscosity: 96-102 KU

Conformance

SCAQMD - complies with Rule 1113, Architectural Coatings

LEED - complies with LEED 2009 and LEEDv4
-Low Emitting Materials

CDPH Section 01350 - tested and passed

MPI - #146

*NOTE: Zero VOC is defined as no VOC containing solvents added in the manufacturing process of this product. Slight traces of VOC are present in additives used in manufacturing. This product has less than half the allowable VOC of the SCAQMD Super Compliant Coatings category.