

Description

V-PRO 5000 (5400 Semi-Gloss) is a zero* VOC, interior/exterior quality latex semi-gloss for use on primed walls and ceilings including masonry, plaster, concrete, acoustic, wood and metal surfaces. This product offers excellent washability, high scrubability, gloss uniformity and has very good non-blocking characteristics. Application on exterior surfaces should be limited to trim, doors and shutters. This product is not for whole house application. **NOTE:** This product contains ingredients which resist the growth of microbes on the surface of the paint film.

Recommended Uses

Designed for commercial, and institutional projects where a durable semi-gloss sheen is required on new interior drywall, plaster, masonry, concrete, block, tilt-ups and acoustic surfaces. NOT recommended for horizontal surfaces such as shelves and paneling.

Colors

Tintable White

Bases: A and D

Packaging

One and five gallon containers

Finish

Semi-Gloss, sheen @ 60° = 35.0 – 45.0%

Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. Glossy or slick surfaces must be scuff sanded prior to application of paint coatings and may require priming.

Primer

Masonry/Concrete (Int.): V-PRO 5001 Primer
(Ext.): 4000 Uniprime

Drywall (New): V-PRO 5001 Primer

Drywall (Existing): 8000 Carefree Prime-ZALL

Wood (Interior/Exterior): 4000 Uniprime
8000 Carefree Prime-ZALL

Metal: 9600 Protec Metal Prime

Glossy Surfaces: 4000 Uniprime

Application

Brush, roll or spray. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Light overspray can be cleaned up with water even after drying. Clean tools and equipment with soap and water.

DISCLAIMER: To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.

Drying Time

Touch: 2 hours

Recoat: 4 hours

Coverage

350 – 400 square feet per gallon, depending on surface.

Mil Thickness

Wet = 4.5 Dry = 1.8

Thinning

Use at package consistency. If thinning is required, use water sparingly.

Composition

Titanium Dioxide 12.6%

Extenders 13.6%

TOTAL PIGMENT 26.2%

Latex Resin 24.3%

Additives 11.5%

Water 38.0%

TOTAL VEHICLE 73.8%

Weights & Measurements +/-3.0%

Solids by Volume: 40.0%

Solids by Weight: 52.4%

VOC: <4 g/l

Weight Per Gal: 10.5 lbs.

Viscosity: 96-102 KU

Conformance

SCAQMD - complies with Rule 1113, Architectural Coatings

LEED - complies with LEED 2009 and LEEDv4
-Low Emitting Materials

MPI - #147

CDPH Section 01350 - tested and passed

*NOTE: Zero VOC is defined as no VOC containing solvents added in the manufacturing process of this product. Slight traces of VOC are present in additives used in manufacturing. This product has less than half the allowable VOC of the SCAQMD Super Compliant Coatings category.