

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name V-PRO 5000 S.G. TINTABLE WHITE

 Product Code
 .5400

 Revision Date:
 07/10/2015

 Print Date:
 2016-01-14

Product Class WATER THINNED PAINT

Color White Recommended use Paint

Restrictions on use No information available

Manufacturer
Vista Paint Corp

Vista Paint Corporation 2020 E. Orangethorpe Ave.

Fullerton, CA 92831 714.680.3800

Emergency Telephone Number(s): 800.535.5053 (Infotrac)

2. HAZARD(S) IDENTIFICATION



GHS Pictograms:

Signal Word: Warning

GHS Classifications: H319 - Eye irritant H315 - Skin Irritant

Hazard Statements: Causes eye and skin irritation

Precautionary Statements: P103 – Read label before use.

P261 – Avoid breathing dust/fume/gas/mist/vapors/spray.

P264 – Wash hands thoroughly after handling. **P273** – Avoid release to the environment.

P281 – Wear protective equipment as required – respirator/safety glasses/gloves.

P285 – In case of inadequate ventilation wear respiratory protection.

P301 + P310 – IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P302 + P350 – IF ON SKIN: Gently wash with plenty of water and soap.

P305 + P351 + P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lens, if present and easy to do. Continue

rinsing.

P501 – Dispose of contents/container in accordance with local/state/federal

regulations.

HNOC: Not Applicable

Other information: No information available

Product Name: V-PRO 5000 S.G. TINTABLE WHITE Vista Paint Corporation Page 1 of 7

COMPOSITION INFORMATION ON COMPONENTS

Hazardous Component CAS Number Weight %

Titanium Dioxide 13463-67-7 12.04

Aluminum Silicate - KAOLIN 1332-58-7 10.65

4. FIRST AID MEASURES

General Advice: No hazards which require special first aid measures.

Rinse thoroughly with plenty of water for at least 15 minutes and **Eye Contact:**

consult a physician.

Skin Contact: Wash off immediately with soap and plenty of water removing all contaminated

clothes and shoes.

Move to fresh air. If symptoms persist, call a physician. Inhalation:

Clean mouth with water and afterwards drink plenty of water. Consult a Ingestion:

physician if necessary.

Most Important Symptoms/Effects: None known.

Treat symptomatically. **Notes To Physician:**

FIRE-FIGHTING MEASURES

NFPA: 1-0-0

Suitable Extinguishing Media: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Protective Equipment And As in any fire, wear self-contained breathing apparatus **Precautions For Firefighters:**

pressure-demand, MSHA/NIOSH (approved or equivalent)

and full protective gear.

Specific Hazards Arising Closed containers may rupture if exposed to fire or extreme

From The Chemical: heat

Product Name: V-PRO 5000 S.G. TINTABLE WHITE **Vista Paint Corporation** Page 2 of 7

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.

Other Information: Prevent further leakage or spillage if safe to do so.

Environmental Precautions: See Section 12 for additional Ecological Information.

Methods For Clean-Up: Soak up with inert absorbent material. Sweep up and shovel into suitable

containers for disposal.

7. HANDLING AND STORAGE

Handling: Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists

or sanding dust. In case of insufficient ventilation, wear suitable respiratory

equipment.

Storage: Keep container tightly closed. Keep out of the reach of children. Keep from

freezing.

Incompatible Materials: No information available

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits

REPORTABLE COMPONENTS	CAS NUMBER	WT %	AGCIH LV/TWA PPM	TV		STEL	nits MG/M3		Vapor Pressure mm Hg @темр
Titanium Dioxide	13463-67-7 1	2.04	10	-	10		-	-	-
Aluminum Silicate - KAOLIN	1332-58-7 1	0.65	-	-	15		_	-	_

Eye/Face Protection: Safety glasses with side-shields.

Skin Protection Protective gloves and impervious clothing.

Respiratory Protection In case of insufficient ventilation wear suitable respiratory equipment.

Engineering Measures: Ensure adequate ventilation, especially in confined areas.

Hygiene Measures: Avoid contact with skin, eyes and clothing. Remove and wash

contaminated clothing before re-use. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Liquid

Odor Little or no odor

Odor Threshold No information available

Product Name: V-PRO 5000 S.G. TINTABLE WHITE Vista Paint Corporation Page 3 of 7

Density (lbs./gal) 10.00 Specific Gravity 1.20

pH No information available
Viscosity (cps) No information available
Solubility No information available
Water Solubility No information available
Evaporation Rate No information available
Vapor Pressure No information available
Vapor Density No information available

Wt. % Solids 50.15 Vol. % Solids 41.42 Wt. % Volatiles 49.85 Vol. % Volatiles 41.42 **Coating VOC** 0.99 g/l **Material VOC** 0.41 g/l 212°F **Boiling Point (°F)** Freezing Point (°F) 32 °F

Flash Point (°F)

Flash Point Method

Flammability (solid, gas)

Upper Explosion Limit

Lower Explosion Limit

Not applicable

Not applicable

Not applicable

Not applicable

Autoignition Temperature (°F)

Decomposition Temperature (°F)

Partition Coefficient (n-octanol/water)

No information available

No information available

10. STABILITY AND REACTIVITY

Reactivity Not Applicable

Chemical Stability Stable under normal conditions.

Conditions To Avoid Prevent from freezing

Incompatible Materials No materials to be especially mentioned.

Hazardous Decomposition Products

None under normal use.

Possibility Of Hazardous Reactions None under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Principal Routes of Exposure: Eye contact, skin contact and inhalation.

Acute Toxicity: No information available

Symptoms No information available

Eye contact May cause slight irritation.

Skin contact Substance may cause slight skin irritation. Prolonged or

repeated contact may dry skin and cause irritation.

Product Name: V-PRO 5000 S.G. TINTABLE WHITE Vista Paint Corporation Page 4 of 7

Inhalation May cause irritation of respiratory tract.

Ingestion Ingestion may cause gastrointestinal irritation, nausea,

vomiting and diarrhea.

Sensitization: No information available

Neurological Effects No information available.

Mutagenic Effects No information available.

Reproductive Effects No information available.

Developmental EffectsNo information available.

Target Organ Effects No information available.

STOT - single exposureNo information available.

STOT - repeated exposureNo information available.

Other adverse effects No information available.

Aspiration Hazard No information available

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical Name	IARC	NTP	OSHA Carcinogen	
	2B - Possible Human		Listed	
Titanium dioxide	Carcinogen			

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

Legend

IARC - International Agency for Research on Cancer NTP - National Toxicity Program OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity EffectsThe environmental impact of this product has not been fully

investigated.

Acute Toxicity to Fish (Titanium Dioxide) LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)

Acute Toxicity to Aquatic Invertebrates No information available

Acute Toxicity to Aquatic Plants

No information available

Product Name: V-PRO 5000 S.G. TINTABLE WHITE Vista Paint Corporation Page 5 of 7

Persistence / Degradability

No information available

Bioaccumulation / Accumulation No information available

Mobility in Environmental Media No information available

Ozone No information available

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method Dispose of in accordance with federal, state, provincial, and local regulations.

Local requirements may vary, consult your sanitation department or

state-designated environmental protection agency for more disposal options.

14. TRANSPORT INFORMATION

DOT Not regulated

ICAO / IATA Not regulated

IMDG / IMO Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA: United States DSL: CanadaYes - All components are listed or exempt.
Yes - All components are listed or exempt.

Federal Regulations

SARA 311/312 hazardous categorization

Acute Health Hazard No
Chronic Health Hazard No
Fire Hazard No
Sudden Release of Pressure Hazard No
Reactive Hazard No

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Aluminum Silicate - 1332-58-7 KAOLIN

Product Name: V-PRO 5000 S.G. TINTABLE WHITE Vista Paint Corporation Page 6 of 7

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs: None

State Regulations

California Proposition 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm at levels less than required for reporting (<0.1%) unless listed in section III.

16. OTHER INFORMATION

HMIS Health: 1* Flammability: 0 Reactivity: 0 PPE: X

Prepared By Vista Paint Corporation

2020 East Orangethorpe Avenue

Fullerton, CA 92831

714.680.3800

SDS Form Date: 2015.12.31

Revision Summary Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

END OF SAFETY DATA SHEET

Product Name: V-PRO 5000 S.G. TINTABLE WHITE Vista Paint Corporation Page 7 of 7