



Description

Acriglo Semi-Gloss is a premium zero* VOC 100% acrylic semi-gloss enamel for exterior and interior surfaces. Acriglo provides good block resistance and durability. It has good adhesion and mildew resistant characteristics. Low odor makes Acriglo suitable for institutional, commercial and residential applications. **NOTE:** This product contains ingredients which resist the growth of microbes on the surface of the paint film.

Recommended Uses

Properly primed drywall, concrete, masonry, wood and metal.

Colors

White, stock colors and custom colors to order.
Bases: A, D & P

Packaging

Quarts, one and five gallon containers

Finish

Semi-Gloss, sheen @ 60° = 60.0 – 64.0%

Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. Glossy or slick surfaces must be scuff sanded prior to application of paint coatings and may require priming.

Primer

Drywall (New):	1100 Hi Build Sealer
Drywall (Existing):	4000 Uniprime
Concrete/Masonry:	4600 Uniprime II
Wood (Exterior):	4200 Terminator II
Wood (Interior):	188 Acrylic Primer
	6600 AquaLac
Ferrous Metal:	9600 Protec Metal Prime White
	9610 Protec Metal Prime Red Oxide
Non-Ferrous Metal:	4800 Metal Pro Primer White
	4810 Metal Pro Primer Red Oxide

Application

Brush, roll or spray. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Clean tools and equipment with soap and water.

Drying Time

Touch:	2 hours
Recoat:	4 - 8 hours, depending on ambient temperature & humidity

Coverage

350 – 400 square feet per gallon, depending on surface.

Mil Thickness

Wet = 4.8	Dry = 1.6
-----------	-----------

Thinning

Use at package consistency. If thinning is required, use water sparingly.

Composition

Titanium Dioxide	14.4%
Extenders	1.2%
TOTAL PIGMENT	15.6%

Acrylic Resin	27.1%
Additives	2.5%
Water	54.8%
TOTAL VEHICLE	84.4%

Weights & Measurements +/-3.0%

Solids by Volume:	35.0%
Solids by Weight:	46.0%
VOC:	<2 g/l
Weight Per Gal:	10.2 lbs.
Viscosity:	94 - 98 KU

Conformance

SCAQMD - complies with Rule 1113, Architectural Coatings

LEED - complies with LEED 2009 and LEEDv4 -Low Emitting Materials

CDPH Section 01350 - tested and passed
MPI - #54, 1147

*NOTE: Zero VOC is defined as no VOC containing solvents added in the manufacturing process of this product. Slight traces of VOC are present in additives used in manufacturing. This product has less than half the allowable VOC of the SCAQMD Super Compliant Coatings category.

DISCLAIMER: To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.

Revised 01.16