



### Description

Coverall Semi-Gloss is a quality interior vinyl acrylic enamel which provides excellent scrubability and washability. For use on new or previously painted drywall, plaster and wood surfaces. Excellent choice for commercial, institutional, new home construction (walls and trim) and property management projects.

### Recommended Uses

Properly primed new and existing interior drywall, plaster, concrete, masonry and wood. Not recommended for wood cabinets. For a block-resistant enamel, use Care-free Semi-Gloss.

### Colors

Stock Colors: 23 Swiss Coffee  
32 Shell White  
33 Off White  
60 Indian White

White-P and custom pastel colors to order.

### Packaging

One and five gallon containers

### Finish

Semi-Gloss, sheen @ 60° = 58.0 – 64.0%

### Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. Glossy or slick surfaces must be scuff sanded prior to application of paint coatings and may require priming.

### Primer

Drywall (New): 1100 Hi-Build Sealer  
Drywall (Existing): 4000 Uniprime  
Concrete/Masonry: 4600 Uniprime II  
Wood: 188 Acrylic Primer  
6600 AquaLac

### Application

Brush, roll or spray. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Clean tools and equipment with soap and water.

### Drying Time

Touch: 2 hours  
Recoat: 4 - 6 hours

### Coverage

300 – 400 square feet per gallon, depending on surface.

### Mil Thickness

Wet = 3.8 Dry = 1.3

### Thinning

Use at package consistency. If thinning is required, use water sparingly.

### Composition

|                      |              |
|----------------------|--------------|
| Titanium Dioxide     | 20.6%        |
| Extenders            | 3.9%         |
| <b>TOTAL PIGMENT</b> | <b>24.5%</b> |

|                      |              |
|----------------------|--------------|
| Resin                | 23.5%        |
| Additives            | 5.1%         |
| Water                | 46.9%        |
| <b>TOTAL VEHICLE</b> | <b>75.5%</b> |

Weights & Measurements +/-3.0%

|                   |             |
|-------------------|-------------|
| Solids by Volume: | 33.8%       |
| Solids by Weight: | 46.2%       |
| VOC:              | 46 g/l      |
| Weight Per Gal:   | 10.2 lbs.   |
| Viscosity:        | 96 - 104 KU |

### Conformance

**SCAQMD** - complies with Rule 1113, Architectural Coatings

**LEED** - complies with LEED 2009  
-Low Emitting Materials

**DISCLAIMER:** To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.

Revised 01.16