

Sanding Sealer TC10

Interior Clear Fast Dry Water-based Sealer

Industrial Coating - Specialty

Description

A clear water-based fast drying sanding sealer, which provides excellent durability, water and chemical resistance and minimal grain raise on properly prepared interior wood.

<u> Drying Time</u>

Touch: 1 hour Recoat: 2 hours

Coverage

850 – 950 square feet per gallon, depending on surface.

Recommended Uses

Woodwork, cabinets, furniture and paneling. Not for use over white and light stains due to yellowing.

Mil Thickness

Vet = 1.7 Dry = 0.8

Colors

Clear

Thinning

Use at package consistency. If thinning is required, use water sparingly.

<u>Packaging</u>

One and five gallon containers

<u>Composition</u>

 Resin
 30.5%

 Additives / Solvents
 13.5%

 Water
 56.0%

 TOTAL VEHICLE
 100.0%

Surface Preparation

All contaminants that may impair adhesion should be removed. Glossy or slick surfaces must be scuff sanded. After application of TC10 allow to dry completely. If necessary lightly sand once more and apply topcoat.

Weights & Measurements +/-3.0%

Solids by Volume: 30.0% Solids by Weight: 32.0% VOC: 195 g/l Weight Per Gal: 8.5 lbs.

Viscosity: 50 - 60 Sec, Zahn #2 Cup

Application

Brush or spray. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Clean tools and equipment with soap and water.

Conformance

SCAQMD - complies with Rule 1113, Architectural Coatings

DISCLAIMER: To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.

Revised 03.15