

# Satin Lacquer

Interior Clear Water-based Satin Lacquer

Industrial Coating - Specialty

A water-based clear satin lacquer, designed for interior applications on cabinets, furniture, paneling and other wood substrates.

### Recommended Uses

Wood primed with sanding sealer.

### Packaaina

Five gallon containers and 55 gallon drums

#### Hinish

Satin, sheen @  $60^{\circ} = 36.0\% + /-2.0\%$ 

### Surface Preparation

All contaminants that may impair adhesion should be removed. TC10 Sanding Sealer must be applied as first coat to minimize grain raise of wood and provide excellent clarity with grain definition.

TC10 Sanding Sealer

### Application

Spray only. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Clean tools and equipment with soap and water.

20 -25 minutes, force dried @

### overage

400 square feet per gallon, depending on surface.

## I hinnina

DO NOT THIN.

### Composition

Clay / Silica 0.8% Acrylic Resin 27.6% Additives / Solvents 19.0% Water 52.6% **TOTAL VEHICLE** 100.0%

Weights & Measurements +/-3.0%

Solids by Volume: 31.0% Solids by Weight: 35.0% VOC: 226 g/l

Weight Per Gal: 8.4 lbs.

Viscosity: 50 - 60 Sec Zahn #2 Cup

#### Contormance

SCAQMD - complies with Rule 1113, Architectural Coatings

DISCLAIMER: To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative Revised 03.15