

Notes:

Job:

Type:

THE GASKINS SERIES

GS04 TORCHIERE - P4 POST TOP

GENERAL DESCRIPTION: The Gaskins Series is a variety of pedestrian scale luminaires for area illumination. The GS04-P4 is a torchiere-style luminaire designed to slip into a Gardco 4" Round Aluminum Pole.

CUTOFF PERFORMANCE: The GS04 provides cutoff performance.

ORDERING

PREFIX	CONFIGURATION	HEIGHT	DISTRIBUTION	WATTAGE	VOLTAGE	FINISH
<input type="text"/>						

Enter the order code into the appropriate box above. Note: Gardco reserves the right to refuse a configuration. Not all combinations and configurations are valid. Refer to notes below for exclusions and limitations. For questions or concerns, please consult the factory.

PREFIX

GS04-P4 P4 Post Top

CONFIGURATION

1 1 way

HEIGHT

8'
10'
12'

DISTRIBUTION

5ID Type V Indirect

WATTAGE


T70CMHE T6 Ceramic Metal Halide with Electronic Ballast
T150CMHE T6 Ceramic Metal Halide with Electronic Ballast

VOLTAGE

UNIV
CMHE units are provided with a ballast that accepts 120V through 277V, 50hz or 60hz.

PAINTED FINISH

BRP Bronze	LSP Light Sandstone
BLP Black	DSP Dark Sandstone
WP White	RBP Red Brick
NP Natural Aluminum	LGP Light Granite
BGP Beige	DGP Dark Granite
OC Optional Color Paint (Specify RAL designation ex: OC-RAL7024)	
SC Special Color Paint (Specify. Must supply color chip)	



© Copyright Gardco Lighting 2004-2007. All Rights Reserved. International Copyright Secured. Gardco Lighting reserves the right to change materials or modify the design of its product without notification as part of the company's continuing product improvement program.

A Genlyte Company

Gardco Lighting
1611 Clovis Barker Road
San Marcos, TX 78666

(800) 227-0758
(512) 753-1000
FAX: (512) 753-7855
www.sitelighting.com



79115-150/0507

THE GASKINS SERIES

GS04 TORCHIERE - P4 POST TOP

SPECIFICATIONS

GENERAL DESCRIPTION: The Gaskins Series is a variety of pedestrian scale luminaires for area illumination. The GS04 luminaire is a torchiere-style luminaire.

P4 MOUNTING: A cast aluminum transition is designed to slip into a Gardco 4" Round Aluminum Pole with no exposed fasteners.

HOUSING/LENS ASSEMBLY: A decorative and functional ribbed one-piece diecasting is attached to the top of the Tower with four (4) 5/16" bolts. This ribbed assembly encloses the optical system and supports the torchiere lens. The torchiere lens is injection molded V825-HID and DR acrylic with a minimum thickness of 1/8". The crowned top is a high impact UV resistant injection molded polymer. The top is fully sealed using an extruded silicone gasket and is hinged for lamp access.

OPTICAL SYSTEMS: The GS04 reflector is composed of specular, extruded and faceted Alzak® components, electropolished, anodized, and sealed. Reflector segments are set in arc tube image duplicating patterns to achieve light control. T6 lamps use a G12 base, with pulse rated porcelain lampholders.

ELECTRICAL: HID electronic ballasts are mounted within a diecast enclosure. Electronic ballasts operate ceramic metal halide lamps only.


FINISH: Each standard color luminaire receives a fade and abrasion resistant electrostatically applied thermally cured triglycidal isocyanurate (TGIC) textured semi-gloss polyester powdercoat finish. Standard colors include Bronze (BRP), Black (BLP), White (WP), Natural Aluminum (NP), Beige (BGP), Light Sandstone (LSP), Dark Sandstone (DSP), Red Brick (RBP), Light Granite (LGP) and Dark Granite (DGP). Consult factory for specifications on custom colors.

LABELS: All luminaires bear U.L. or C.U.L. (where applicable) Wet Location labels.

FULL CUTOFF PERFORMANCE: Full cutoff performance means a luminaire distribution where zero candela intensity occurs at an angle of 90° above nadir. Additionally, the candela per 1000 lamp lumens does not numerically exceed 100 (10 percent) at a vertical angle of 80° above nadir. This applies to all lateral angles around the luminaire.

CUTOFF PERFORMANCE: Cutoff performance means a luminaire distribution where the candela per 1000 lamp lumens does not numerically exceed 25 (2.5 percent) at an angle at or above 90° above nadir, and 100 (10 percent) at a vertical angle of 80° above nadir. This applies to all lateral angles around the luminaire.

DIMENSIONS



NOTE: Factory supplied template must be used when setting anchor bolts. Gardco Lighting will not honor any claim for incorrect anchorage placement from failure to use factory supplied templates.

© Copyright Gardco Lighting 2004-2007. All Rights Reserved. International Copyright Secured. Gardco Lighting reserves the right to change materials or modify the design of its product without notification as part of the company's continuing product improvement program. Solite is a Registered Trademark of AFG Industries.

A Genlyte Company

Gardco Lighting
1611 Clovis Barker Road
San Marcos, TX 78666

(800) 227-0758
(512) 753-1000
FAX: (512) 753-7855
www.sitelighting.com



79115-150/0507