

# Caretaker™ LED

## Product Specification by Brand

Product Features		Lumark Caretaker LED Area Luminaire	Streetworks Caretaker LED Roadway and Area Luminaire
Lumen Package		5,213	4,814 and 6,910
Correlated Color Temperature (CCT)		5000K	4000K and 5000K
Distribution		Type V	Type II and Type V
Luminaire Wattage		50W	48W and 73W
Photocontrol		Commercial Grade NEMA Twistlock Photocontrol Included	NEMA PC Receptacle Standard, Photocontrol Not Included
Color		Raw Aluminum Unfinished	Standard Colors or Raw Aluminum Unfinished
	ANSI Wattage Label	No	Included
	Terminal Block	No	Included
	Surge Protection	6kV Surge Included	6kV Surge Included, 10kV UL 1449 Surge Protection Optional
	Wall-Wood Pole Mounting Bracket	Included	Optional
	Small Acrylic Refractor	Optional	Optional
	NEMA Standard Refractor	Optional	Optional
	Two-Bolt Slipfitter (1-1/4" - 2" Pipe)	Included	Included
	Wood Pole Pipe Arm	Not Available	Optional
	Tool-less Access	Not Available	Optional



**Lumark**  
(8 LEDs Shown)



**Streetworks**  
(12 LEDs Shown)

**Cooper Lighting**  
by **EATON**