


# HP-WS Perimeter Slot Wall Bracket Mount Spackle Flange Installation Instructions Overview



**Helpful Video**




0-10V Dimming

HP-WS Perimeter Slot Wall Bracket Mount Spackle Flange Installation Instructions

Step 1 - Wall Rail Mounting Location

FINELITE®

Better Lighting




Distance between wall rail and nearest perpendicular wall.

Luminaire Width Configuration	Inside Corner: X Min – X Max = End of wall rail to wall	
	X Min	X Max
4W	8"	14"
6W	10"	16"


Luminaire Width Configuration	Outside Corner: X Min – X Max = End of wall rail to wall	
	X Min	X Max
4W	1"	8"
6W	1"	7"

Lay out all wall rails on the floor in front of the wall they will be mounted on. Place them end-to-end, using the table to check the amount of gap you need between the end rails and their closest perpendicular wall, equal on each side.



Note: Tolerances on dimensions are  $\pm 1/16"$

Measure wall rail height. Use the provided table to find the height and mark it on all the walls.



Install the wall rail(s), using appropriate #10 screws (by others) to wall studs. (Note: For X reference use chart above.)


#10 Screws  
(by others)

CONTINUED

# HP-WS Perimeter Slot Wall Bracket Mount Spackle Flange Installation Instructions


## Step 1 - Wall Rail Mounting Location

### Mounting



Measure gaps **A** and **B** as indicated above.


### Corner Wall Rail



Separate the corner wall rail in half.

Using a chop saw (carbide tipped blade recommended) cut the "A" corner wall rail to length **A**, referencing the mitered end with a jog. Then cut the "B" corner wall rail to length **B**, referencing the mitered end. **Repeat steps 2 and 3 for all walls.**


### Install Corner Wall Rails



Install the corner wall rails using appropriate #10 screws (by others). Where the corner wall rails meet at a corner, make sure the "A" corner wall rail jog feature overlaps the "B" corner wall rail. Install the wall support corner bracket by sitting it on top of the corner wall rails and using appropriate #10 screws (by others) to attach it to the corner. **Repeat for all corners.**



#10 Screws  
(by others)




Wall Support  
Corner Bracket  
(provided)


# HP-WS Perimeter Slot Wall Bracket Mount Spackle Flange Installation Instructions

## Step 2 - Feed Locations & Options


Top Feed (standard)





Wall Feed (optional)



Endcap Feed (optional)



 #8-18 x 1/4" Screw(s)  
(provided)

 #10-32 Screw  
(provided)

CONTINUED




# HP-WS Perimeter Slot Wall Bracket Mount Spackle Flange Installation Instructions

## Step 2 - Feed Locations & Options

**FINELITE®**  
*Better Lighting*


**Top Feed** Top View

Luminaire Length	C (in)
2'	5
3'	5
4'	12
6'	12




**Top Feed Location (standard)**  
Use chart above to find measurement of **C** for feed location

**Wall Feed** Back View



	D (in)
2" Depth	3-5/16
4" Depth	5-5/16
6" Depth	7-5/16

**Endcap Feed** Side View




Endcap Size	F (in)	G (in)
4'	1-3/16	1-7/8
6'	2	1-7/8

# HP-WS Perimeter Slot Wall Bracket Mount Spackle Flange Installation Instructions


## Step 3 - Starter Luminaire

### 1. Remove Tapered Optic & Diffuser Bottom-Up View




If tapered optic is included, remove the two #4-24 x 1/4" self drilling screws (provided) from starter luminaire. Then remove the diffuser from the starter luminaire and set it aside to keep it from getting dirty or damaged. If part of a longer run, diffuser will be reinstalled back into original luminaire.

### 2. Mounting on the Wall Rail Side View





Mount the starter luminaire to the wall rail as shown, aligning the end of the starter luminaire body to the start of the main wall rail. Make sure the wall rail clips grab the top of the wall rail.


### 3. Mounting on the Wall Rail Side View



On the starter luminaire, tighten the #8-18 x 1/2" screws (provided) that goes through the carrier assembly until the carrier meets the bottom surface of the wall rail. Secure the starter luminaire to the wall rail with the #8-18 x 1/4" screws (provided) going through the wall rail clips. Secure all carrier clips by rotating them 90° degrees counter-clockwise.

 #4-24 x 1/4" Self Drilling Screws (provided)

 #8-18 x 1/4" Screws (provided)

 #8-18 x 1/2" Screws (provided)


HP-WS Perimeter Slot Wall Bracket Mount Spackle Flange Installation Instructions

Step 4 - Joining Luminaires

**FINELITE®**  
Better Lighting

1. Align Starter and Joiner/Ender


Top View




If your joiner/ender has a telescoping arm assembly, retract it to ensure it will not be damaged during install. Mount the luminaire to the wall rail as shown. Make sure the wall rail clips grabs the top of the wall rail.

2. Plug-together Wiring

Top View



Connect the plug-together wiring. Slide the joiner/ender luminaire over the aligner plate on the installed luminaire. Make sure the holes are aligned on the plate, then fasten the joiner/ender luminaire to the aligner plate using #8-18 x 1/4" screw (provided).


 #8-18 x 1/4" Screw  
(provided)

CONTINUED

# HP-WS Perimeter Slot Wall Bracket Mount Spackle Flange Installation Instructions


## Step 4 - Joining Luminaires

### 3. Secure Joiner/Ender Top View





Secure the joiner/ender luminaire to the wall rail with #8-18 x 1/4" screws (provided) going through the wall rail clips.  
**Repeat steps 4 if you have a long run with more luminaires on the same wall. Repeat steps 3 for the next wall.**

### 4. Secure the Carrier Assembly Side View



On all mounted luminaires, tighten the #8-18 x 1/2" screws (provided) that goes through the carrier assembly until the carrier meets the bottom surface of the wall rail. Secure carrier clips by rotating them 90° degrees counter-clockwise.


 #8-18 x 1/4" Screw  
(provided)

 #8-18 x 1/2" Screw  
(provided)

# HP-WS Perimeter Slot Wall Bracket Mount Spackle Flange Installation Instructions


## Step 5A - Inside Corner

### 1. Connect Corner Joint Top-Down View




Connect the corner joint to the right telescoping arm using a #8-18 x 1/4" screw (provided).

### 2. Connect Flex Conduit Bottom-Up View





Connect the through wiring using flex conduit and make sure the flex conduit goes above the corner support bracket. To connect flex conduit, remove telescope endcap 2x #8-18 x1/4" screws (provided) for access.

### 3. Connect Flex Conduit Top-Down View



For all non-power feed corners that need through wiring, connect the wiring for the two wall runs using a flex conduit and telescope endcaps. The endcaps are connected using #8-18 x 1/4" screws (provided). Connect wiring from both luminaire ends to the flex conduit. Then, extend the telescoping arm assembly from the luminaire on the "A" corner up until it meets the wall support corner bracket. Extend the telescoping arm assembly from the luminaire on the "B" corner so it aligns with the inside corner joint as shown. Pin the telescoping arms together from below the luminaire using a #8-18 x 1/4" screw (provided).




CONTINUED



# HP-WS Perimeter Slot Wall Bracket Mount Spackle Flange Installation Instructions


## Step 5A - Inside Corner

### 4. Telescope Spackle Flange Subassembly Top View



Prep the telescope spackle flange (provided) for the telescope spackle flange corner bracket as shown, we recommend using tin snips. Connect the two pieces to the telescope spackle flange corner bracket by sliding the tabs through the slots and bending the tabs back.


### 5. Telescope Spackle Flange Subassembly Top View




Remove the nuts from the section on the luminaire where the telescope spackle flange and the luminaire studs overlap. Place the telescope spackle flange subassembly onto the corner. Reattach nuts to fasten the telescope spackle flange subassembly to corner.



Nut  
(provided)



Telescope Spackle Flange  
Corner Bracket  
(provided)




Telescope Spackle Flange  
(provided)

# HP-WS Perimeter Slot Wall Bracket Mount Spackle Flange Installation Instructions


## Step 5B - Outside Corner

### 1. Connect Corner Joint Bottom-Up View




Connect the corner joint to the right telescoping arm using a #8-18 x 1/4" screw (provided).

### 2. Connect Flex Conduit Bottom-Up View



Connect the through wiring using flex conduit and be sure the flex conduit goes above the corner support bracket. To connect flex conduit, remove telescope endcap 2x #8-18 x1/4" screws (provided) for access.

 #8-18 x 1/4" Screw  
(provided)

CONTINUED

HP-WS Perimeter Slot Wall Bracket Mount Spackle Flange Installation Instructions


Step 5B - Outside Corner

FINELITE®

Better Lighting

3. Connect Telescoping Arms


Bottom-Up View



Mount right side telescoping arm to corner support bracket. Connect left telescoping arm and fasten to right telescope arm with #8-18 x 1/4" screw (provided).

4. Telescope Spackle Flange Subassembly

Top View




If necessary, snip at perforations where it will meet the corner. Be sure to leave tabs.


Prep the telescope spackle flange for the telescope spackle flange corner bracket as shown, we recommend using tin snips. Connect the two pieces to the telescope spackle flange corner bracket by sliding the tabs through the slots and bending the tabs back.

5. Telescope Spackle Flange Subassembly

Top View



Remove the #10-32 nuts from the section where the telescope spackle flange and the luminaire studs overlap. Place the telescope spackle flange subassembly onto the corner. Reattach nuts to fasten the telescope spackle flange subassembly to corner.

 #8-18 x 1/4" Screw  
(provided)

 Nut  
(provided)

 Telescope Spackle Flange  
Corner Bracket  
(provided)

 Telescope Spackle Flange  
(provided)

Finelite, Inc. • 30500 Whipple Road • Union City, CA 94587-1530 • (510) 441-1100 • Fax: (510) 441-1510 • [www.finelite.com](http://www.finelite.com)

**Note:** All power connections to be installed to local/national codes by a Certified Electrician.

HP-WS Perimeter Slot Wall Bracket Mount Spackle Flange Installation Instructions

Step 6 - Straight Telescope

**FINELITE®**  
Better Lighting

1. Extend Straight Telescope

Bottom-Up View

Extend telescoping arm to wall, ensuring it is level. Mark where the telescope wall support bracket will be mounted.

2. Mount Support Bracket


Bottom-Up View

Mount support bracket to wall using appropriate #10 screws (by others).

3. Hook Telescope

Bottom-Up View

Hook the telescoping arm onto the support bracket using the slot provided.




#10 Screws  
(by others)

# HP-WS Perimeter Slot Wall Bracket Mount Spackle Flange Installation Instructions


## Step 6 - Straight Telescope

### 4. Telescope Spackle Flange Subassembly



Snip off the end of the telescope spackle flange that will be mounted to the wall.

### 5. Telescope Spackle Flange Subassembly Bottom-Up View



Remove the nut from the stud that overlaps the telescope spackle flange. Fasten the spackle flange to the wall using two #10 screws (by others). Trimming between the oval slots may be necessary if the stud interferes with the flange. Fasten the nut back onto the stud.



#10 Screws  
(by others)



Nut  
(provided)




HP-WS Perimeter Slot Wall Bracket Mount Spackle Flange Installation Instructions

Step 7 - Luminaire Closure

FINELITE®

Better Lighting


1. Support Blocking



	4" Width	6" Width
2" Height	X = 4-5/8" Y = 5-1/8"	X = 6-5/8" Y = 5-1/8"
4" Height	X = 4-5/8" Y = 7-1/8"	X = 6-5/8" Y = 7-1/8"
6" Height	X = 4-5/8" Y = 9-1/8"	X = 6-5/8" Y = 9-1/8"


Provide appropriate support blocking for proper drywall installation and around the luminaire using the table above. Fasten the luminaire using appropriate #10 screws (by others) through the spackle flanges. The image shown is the 4"W x 2"H configuration. Make sure to leave ample space around wiring conduit.

2. Secure Spackle Flange Bottom-Up View




Mount spackle flange to drywall ceiling using appropriate #10 screws (by others).

3. Measure Diffusers Bottom-Up View



Diffuser length "X" is always measured along the longest edge. Measure the overall length for square-edged lengths. Measure from the square edge to the tip of a mitered edge. Cut the diffuser to "X" minus 1/16". For example, if "X" is 8'6", cut the diffuser to 8' 5-15/16". This difference accounts for thermal expansion and helps to avoid light leaks. Diffusers should be cut at a room temperature between 70°F and 73°F. Contact the factory if cutting at a temperature outside that range.

4. Finish it up! Bottom-Up View



Replace diffusers and reinstall tapered optics using #4-24 x 1/4" self drilling screws (provided). Turn power on to luminaire.

**#10 Screws**  
(by others)

**#4-24 x 1/4" Self Drilling Screws**  
(provided)

**Mud Guard**  
(provided)