

## Skylight LED Flat Panel Lights



2x2' version



2x4' version



Top view (2x2' version, mounted enclosure shown on upper left)



LED driver (attached to panel)

Skylight LED Flat Panel Light combines smooth, diffuse light output with an extremely low profile – making it easy on the eyes and easy to install in any ceiling.

The unique light output of the Skylight comes from the LEDs embedded along the interior sides of each 2x2' and 2x4' panel, eliminating glare. This light is refracted through a diffuser lens to ensure soft, even illumination – perfect for space requiring high quality ambient lighting.

At less than 0.5 inch tall (2.25 inches with power supply enclosure), the LED Panel Light offers industry-leading versatility and ease of installation. Wherever it fits, it sits; simply wire the included LED driver to line voltage in your wall or ceiling.

Skylight LED Flat Panel Light is UL listed and DLC qualified to ensure safety and reliability. Each unit is rated to last over 50,000 hours, and comes backed by LED Waves' 5 year warranty.

Mounting hardware included.



### Technical Data

|                              |   |
|------------------------------|---|
| <b>Part number (SKU)</b>     | 2x2' version: SL1-2x2-36W-4000K-D<br>2x4' version: SL1-2x4-52W-4000K-D  |
| <b>Color Temperature</b>     | 4,000 Kelvins   |
| <b>Light Output</b>          | 2 x 2' version: 3,420 lumens<br>2 x 4' version: 5,200 lumens  |
| <b>Wattage</b>               | 2 x 2' version: 36 Watt<br>2 x 4' version: 52 Watt  |
| <b>Input Voltage</b>         | 100~277VAC, 50/60Hz   |
| <b>Dimming</b>               | 0-10VDC dimmer compatible   |
| <b>Lifespan</b>              | 50'000 hours  |
| <b>Certifications</b>        | UL Listed, DLC qualified  |
| <b>Operating Temperature</b> | 25 ~ 122F° (-4 ~ 50C°)  |
| <b>Warranty</b>              | 5 years   |
| <b>Dimensions</b>            | 2 x 2' version:<br>23.75 x 23.75 x 0.43" (603 x 603 x 11mm)<br>2 x 4' version:<br>23.75 x 47.75 x 0.43" (603 x 1213 x 11mm) |